



Air Filter

AF10 to AF60

JIS Symbol
Air Filter



Air Filter with Auto Drain



AF20

AF40

How to Order

AF **30** - **03** **BD** - **5** - **1**

① ② ③ ④ ⑤

Made to Order

(Refer to page 334 through to 336 for details.)

- Option/Semi-standard: Select one each for a to f.
- Option/Semi-standard symbol: When more than one specification is required, indicate in alphanumeric order.
Example) AF30-03BD-2R

		Symbol	Description	1									
				Body size									
				10	20	30	40	50	60				
2	Thread type	Nil	Metric thread (M5)	●	—	—	—	—	—				
		Rc	—	●	●	●	●	●					
		N ^{Note 1)}	NPT	—	●	●	●	●	●				
		F ^{Note 2)}	G	—	●	●	●	●	●				
+													
3	Port size	M5	M5	●	—	—	—	—	—				
		01	1/8	—	●	—	—	—	—				
		02	1/4	—	●	●	—	—	—				
		03	3/8	—	—	●	●	—	—				
		04	1/2	—	—	—	●	—	—				
		06	3/4	—	—	—	●	●	—				
		10	1	—	—	—	—	●	●				
+													
4	Option	a	Mounting	Nil	Without mounting option		●	●	●	●	●	●	
				B ^{Note 3)}	With bracket		—	●	●	●	●	●	●
	+												
	b	Float type auto drain	Nil	Without auto drain		●	●	●	●	●	●		
			C	Float type auto drain (N.C.)		●	●	●	●	●	●		
			D	Float type auto drain (N.O.)		—	—	●	●	●	●		
	+												
	5	Semi-standard	c	Bowl ^{Note 4)}	Nil	Polycarbonate bowl		●	●	●	●	●	●
					2	Metal bowl		●	●	●	●	●	●
					6	Nylon bowl		●	●	●	●	●	●
8					Metal bowl with level gauge		—	—	●	●	●	●	
C					With bowl guard		—	●	—	—	—	—	
6C					Nylon bowl with bowl guard		—	●	—	—	—	—	
+													
d			Drain port ^{Note 5)}	Nil	With drain cock		●	●	●	●	●	●	
				J ^{Note 6)}	Drain guide 1/8		—	●	—	—	—	—	
					Drain guide 1/4		—	—	●	●	●	●	
				W ^{Note 7)}	Drain cock with barb fitting: For ø6 x ø4 nylon tube		—	—	●	●	●	●	
+													
e			Flow direction	Nil	Flow direction: Left to right		●	●	●	●	●	●	
				R	Flow direction: Right to left		●	●	●	●	●	●	
+													
f			Pressure unit	Nil	Name plate and caution plate for bowl in imperial units: MPa		●	●	●	●	●	●	
				Z ^{Note 8)}	Name plate and caution plate for bowl in imperial units: psi. °F		○ ^{Note 9)}	○ ^{Note 9)}	○ ^{Note 9)}	○ ^{Note 9)}	○ ^{Note 9)}	○ ^{Note 9)}	

Note 1) Drain guide is NPT1/8 (applicable to the AF20) and NPT1/4 (applicable to the AF30 to AF60). The auto drain port comes with ø3/8" one-touch fitting (applicable to the AF30 to AF60).

Note 2) Drain guide is G1/8 (applicable to the AF20) and G1/4 (applicable to the AF30 to AF60).

Note 3) A bracket is not assembled and supplied loose at the time of shipment. Including 2 mounting screws

Note 4) Refer to Chemical Data on page 287 when selecting a case material.

Note 5) Float type auto drain: The combination of C and D is not possible.

Note 6) Without a valve function

Note 7) Metal bowl: The combination of 2 and 8 is not possible.

Note 8) For thread type: M5 and NPT. This product is for overseas use only according to the new Measurement Law. (The SI unit type is provided for use in Japan.)

Note 9) ○: For thread type: M5 and NPT only

Air Filter *Series AF10 to AF60*

Standard Specifications

Model	AF10	AF20	AF30	AF40	AF40-06	AF50	AF60
Port size	M5 x 0.8	1/8, 1/4	1/4, 3/8	1/4, 3/8, 1/2	3/4	3/4, 1	1
Fluid	Air						
Ambient and fluid temperature	−5 to 60°C (with no freezing)						
Proof pressure	1.5 MPa						
Maximum operating pressure	1.0 MPa						
Nominal filtration rating	5 μm						
Drain capacity (cm³)	2.5	8	25	45			
Bowl material	Polycarbonate						
Bowl guard	—	Semi-standard	Standard				
Mass (kg)	0.06	0.18	0.22	0.45	0.49	0.99	1.05

Options/Part No.

Optional specifications		Model						
		AF10	AF20	AF30	AF40	AF40-06	AF50	AF60
Bracket assembly ^{Note 1)}		—	AF20P-050AS	AF30P-050AS	AF40P-050AS	AF40P-070AS	AF50P-050AS	AF50P-050AS
Float type auto drain ^{Note 2) Note 3)}	N.C.	AD17	AD27	AD37	AD47			
	N.O.	—	—	AD38	AD48			

Semi-standard/Bowl Assembly Part No.

Semi-standard specifications						Model						
Bowl material	Note 2) Note 3) Float type auto drain		Note 3) With drain guide	With barb fitting	With bowl guard	AF10	AF20	AF30	AF40	AF40-06	AF50	AF60
	N.C.	N.O.										
Polycarbonate	—	—	—	—	●	—	C2SF-C	—	—			
	●	—	—	—	●	—	AD27-C	—	—			
	—	—	●	—	—	—	C2SF-J	C3SF-J	C4SF-J			
	—	—	—	●	—	—	—	C3SF-W	C4SF-W			
	—	—	●	—	●	—	C2SF-CJ	—	—			
Nylon	—	—	—	—	—	C1SF-6	C2SF-6	C3SF-6	C4SF-6			
	—	—	—	—	●	—	C2SF-6C	—	—			
	●	—	—	—	—	AD17-6	AD27-6	AD37-6	AD47-6			
	—	●	—	—	—	—	—	AD38-6	AD48-6			
	●	—	—	—	●	—	AD27-6C	—	—			
	—	—	●	—	—	—	C2SF-6J	C3SF-6J	C4SF-6J			
	—	—	—	●	—	—	—	C3SF-6W	C4SF-6W			
Metal	—	—	●	—	●	—	C2SF-6CJ	—	—			
	—	—	—	—	—	C1SF-2	C2SF-2	C3SF-2	C4SF-2			
	●	—	—	—	—	AD17-2	AD27-2	AD37-2	AD47-2			
	—	●	—	—	—	—	—	AD38-2	AD48-2			
Metal bowl with level gauge	—	—	●	—	—	—	C2SF-2J	C3SF-2J	C4SF-2J			
	●	—	—	—	—	—	—	C3LF-8	C4LF-8			
	—	●	—	—	—	—	—	AD37-8	AD47-8			
	—	—	—	—	—	—	—	AD38-8	AD48-8			
	—	—	●	—	—	—	—	C3LF-8J	C4LF-8J			

Note 1) Assembly of a bracket and 2 mounting screws

Note 2) Minimum operating pressure: N.O. type—0.1 MPa; N.C. type—0.1 MPa (AD17/27) and 0.15 MPa (AD37/47). Please contact SMC for psi and °F unit specifications.

Note 3) Please consult with SMC for details on drain piping to fit NPT or G port sizes.

Note) • Bowl O-ring is included for the AF20 to AF60.

• Bowl assembly for the AF30 to AF60 models comes with a bowl guard (steel band material). (except when the bowl material is metal)

AC

AF□

AR

AL

AW□

A□G

AV

AF800
AF900