

TECHNICAL DATASHEET

Update : 26/02/2019

UNC TAP - SPIRAL FLUTE - HSS 3% VANADIUM - MULTI-MATERIALS



Description

UNC thread . Blind hole taps



Characteristics

Ref.	EAN	Threading (inch)	Threading diameter (inch)	No. of threads per inch	Angle of helix °	Total length mm	Body material	Tolerance	Drilling diameter mm	Tail diameter mm	Square drive adapter mm
864971	3660338194078	UNC	6	32	40	56	HSSE 3% Vanadium	2B	2,7	4	3
864972	3660338194085	UNC	8	32	40	63	HSSE 3% Vanadium	2B	3,5	4,5	3,4
864973	3660338194092	UNC	10	24	40	70	HSSE 3% Vanadium	2B	3,8	6	4,9
864974	3660338194108	UNC	12	24	40	80	HSSE 3% Vanadium	2B	4,5	6	4,9
864975	3660338194115	UNC	1/4	20	40	80	HSSE 3% Vanadium	2B	5,1	7	5,5
864976	3660338194122	UNC	5/16	18	40	90	HSSE 3% Vanadium	2B	6,5	8	6,2
864970	3660338194061	UNC	5	40	40	56	HSSE 3% Vanadium	2B	2,65	3,5	2,7
864977	3660338194139	UNC	3/8	16	40	90	HSSE 3% Vanadium	2B	7,9	9	7
864978	3660338194146	UNC	7/16	14	40	100	HSSE 3% Vanadium	2B	9,3	8	6,2
864979	3660338194153	UNC	1/2	13	40	110	HSSE 3% Vanadium	2B	10,7	9	7
864980	3660338194160	UNC	9/16	12	40	110	HSSE 3% Vanadium	2B	12,3	11	9
864981	3660338194177	UNC	5/8	11	40	110	HSSE 3% Vanadium	2B	13,5	12	9
864982	3660338194184	UNC	3/4	10	40	125	HSSE 3% Vanadium	2B	16,5	14	11
864983	3660338194191	UNC	7/8	9	40	140	HSSE 3% Vanadium	2B	19,3	18	14,5
864984	3660338194207	UNC	1	8	40	160	HSSE 3% Vanadium	2B	22,25	18	14,5
867025	3660338210624		4		40	56				3,5	2,7