

CRACK'R SAFETY GLASSES

Clear Version AR – Ref. 887639

Clear Version AR AB – Ref. 887640



Description:

Lightweight and comfortable safety glasses with a wraparound, rimless design. Thin and flexible temples. Molded nose bridge. Protects against UVA and UVB rays, filtering 99.9% of the spectrum. Weight: 23.3 g

Colors:

Colourless eyepieces. Black temples.

Materials:

Lenses and temples made of polycarbonate

Screws made of stainless steel

Key Features

Curved lenses are designed to provide an excellent field of vision.

Features:

Lens curvature: 10.5

Lens thickness: 2 mm

Coatings: Anti-scratch and anti-fog (887640 model only)

FT Protection: Against high-speed particles at extreme temperatures (point 7.34 of EN166:2001). This corresponds to the impact of a 6 mm steel ball with a minimum mass of 0.86 g launched at 45 m/s.

Lenses: 2C-1.2 G 1 FT CE

Frame : CE EN166 FT

Certifications:

EN166: 2001

Cleaning & Maintenance Instructions :

Clean with warm water and dry using a soft, dry, lint-free, and non-abrasive cloth.

When not in use, do not leave the glasses outside their packaging or transport them unprotected alongside other items such as tools or metal objects._

Packaging:

Boxes of 300 units.

LENS MARKING

Optical class symbols: 1. Continuous work

Mechanical strength symbols: F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s Maximum protection for glasses. T. The letter T, immediately after the mechanical strength symbol, authorises use for high-speed particles at extreme temperatures.

FRAME MARKING

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc. F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s Maximum protection for spectacles. T. The letter T, immediately after the mechanical strength symbol, authorizes use for high speed particles at extreme temperatures.