

Solenoid coil VACC-S13-18-K4-1UF-EX4ME

Part number: 8109399

FESTO



Data sheet

Feature	Value
Type code	VACC
Actuation type	Electrical
Mounting position	Any
Switching position indication	no
Internal fuse protection	Fuse
Duty cycle	100%
Insulation class	H
Coil characteristics	24 V DC: 1.8 W 24 V AC: 40/65 Hz, power 1.8 VA
Permissible voltage fluctuations	-15 % / +10 %
ATEX category gas	II 2G
Type of ignition protection for gas	Ex eb mb IIC T6, T5, T4 Gb
ATEX category for dust	II 2D
Type of (ignition) protection for dust	Ex tb IIIC T85°C, T95°C, T130°C Db
Explosion protection certification outside the EU	EPL Gb (IEC-EX) EPL Db (IEC-EX)
Explosive ambient temperature	T5, T95°C: -30°C ≤ Ta ≤ +60°C T6, T85°C: -30°C ≤ Ta ≤ +50°C T4, T130°C: -30°C ≤ Ta ≤ +60°C
Certificate issuing authority	IECEX BVS 15.0075X BVS 15ATEXE029X
Explosion prevention and protection	Zone 1 (ATEX) Zone 21 (ATEX) Zone 21 (IEC-EX) Zone 2 (ATEX) Zone 1 (IEC-EX) Zone 22 (ATEX)
CE marking (see declaration of conformity)	as per EU explosion protection directive (ATEX)
Degree of protection	IP65
Product weight	330 g
Electrical connection	Terminal box, cable entry thread M20x1.5
Note on materials	RoHS-compliant Contains paint-wetting impairment substances