

Semi-rotary drives DSR/DSRL

Peripherals overview and type codes

Mounting attachments and accessories				
	Description	DSR	DSRL	→ Page/Internet
1	Foot mounting HSR-...-FW	■	■	12
2	Freewheel unit FLSR-...-L/R	■	–	14
3	Flange mounting FSR	■	–	12
4	Push-on flange FWSR	■	–	13
5	Mounting kit WSR-...	■	■	17
6	Mounting kit WSR-12 ... 40	■	■	16
7	Mounting kit WSR-10/12-K	■	■	16
8	Micro switch S-3-BE-SW	■	■	19
9	Micro switch S-3-BE	■	■	19
10	Micro stem actuated valve SO-3-PK-3-B, S-3-PK-3-B	■	■	20
11	Proximity sensors SIEN	■	■	20
12	Push-in L-fitting QSL	■	■	qs
13	One-way flow control valve GRLA	■	■	20

DSRL		–	10	–	180	–	P	–	FW								
<table border="1"> <tr> <th>Type</th> <td></td> </tr> <tr> <td>Double-acting</td> <td></td> </tr> <tr> <td>DSR</td> <td>Semi-rotary drive with spigot shaft</td> </tr> <tr> <td>DSRL</td> <td>Semi-rotary drive, with flanged, hollow drive shaft</td> </tr> </table>										Type		Double-acting		DSR	Semi-rotary drive with spigot shaft	DSRL	Semi-rotary drive, with flanged, hollow drive shaft
Type																	
Double-acting																	
DSR	Semi-rotary drive with spigot shaft																
DSRL	Semi-rotary drive, with flanged, hollow drive shaft																
<table border="1"> <tr> <th>Piston Ø [mm]</th> <td></td> </tr> </table>										Piston Ø [mm]							
Piston Ø [mm]																	
<table border="1"> <tr> <th>Swivel angle [°]</th> <td></td> </tr> </table>										Swivel angle [°]							
Swivel angle [°]																	
<table border="1"> <tr> <th>Cushioning</th> <td></td> </tr> <tr> <td>P</td> <td>Non-adjustable at either end</td> </tr> </table>										Cushioning		P	Non-adjustable at either end				
Cushioning																	
P	Non-adjustable at either end																
<table border="1"> <tr> <th>Shaft</th> <td></td> </tr> <tr> <td></td> <td>Spigot shaft</td> </tr> <tr> <td>FW</td> <td>Drive shaft</td> </tr> </table>										Shaft			Spigot shaft	FW	Drive shaft		
Shaft																	
	Spigot shaft																
FW	Drive shaft																