

SPECTACLES G-HIVIZ

Item #	EAN	Product
854317	3660338101175	Clear
854318	3660338101182	Smoke

Description

Standard : EN 166 - EN 170 – EN172 (smoked version)

Innovative design glasses with integrated lateral protection.

Very modern and anti-slip legs.

High visibility mount/ Integrated eyebrow protection.

Non-slip nose

Applications All types of industries, inside or outside, construction and building, maintenance, machinery drivers, grinding, industry, sport, laboratories, assembly shops etc.

Characteristics

- Extremely lightweight and modern safety eyewear.
- Outstanding field of vision and exceptional protection.
- Molded-in nose bridge provides uncompromised comfort and fit.
- Single-piece lens that will fit most faces.
- ISO9001 manufacturing ensuring a reliable and durable quality
- Protection against mechanical risks: projections of solids, of chips, particles, strokes ...
- Protection against UV rays.
- Anti-mist and scratch resistant treatments.
- Ideal for been seen from afar.
- Ultra-light: 26g.



Instructions & storage

Check carefully that the equipment is suitable for the intended use.

Replace the used or deteriorated products.

Read the user information sheet enclosed with the product before use.

Standards and certifications

UK
CA

EN166: 2001, EN170, EN172 (smoke version) Lens marking : 2C-1.2 1 FT

Lens marking (smoke) : 5-2.5 1 FT

Frame marking : CE EN166 FT

Mechanical protection	Symbol FT	Impact resistant against high speed particles at high temperatures (corresponds to the impact of a steel ball with a diameter of 6 mm and a minimum mass of 0.86 g launched at 45 m/s).
Optical quality	Symbole 1	Class 1 continuous works (better quality).
Scale number	Symbole 2C.1.2 Smoke 5-2.5	Colour perception: may be impaired unless marked «2C». Typical application: for use with sources which emit predominantly ultraviolet radiation at wavelengths shorter than 313 nm and when glare is not an important factor: this covers the UVC and most of the UVD Bands (b). Typical sources: Low pressure mercury lamps such as lamps used to stimulate fluorescence or «black lights», mercury lamps, germicidal lamps. (b) U.V.B: 280 nm to 315 nm et U.V.C: 100 nm to 280 nm.

Packaging

- Carton of 200 units/ Box of 10 units/ Each unit individually packaged.