


2/2 Normally Closed

BRASS

PIPE MOUNTING

NORMALLY CLOSED



Port size	Orifice Ø	Flow factors		Operating Pressure Differential			Fluid Temp.		Seat Seal	Valve Order Number	Valve Type	Coil Group	Dwg. No.
		Kv l/min	KV m³/h	Min bar	Max(MOPD) AC bar	DC bar	Min °C	Max °C					
BSP	mm												
3/8"	13	50	3	0.1	20	20	-10	90	NBR	443776W	7321BIN00	2.0/2.1/2.2	1
	13	50	3	0.1	20	20	-10	90	NBR	443777W ₂	7321BIN01	2.0/2.1/2.2	1
	13	50	3	0.1	10	10	-10	140	EPDM	443778W ₁	7321BIH00	2.0/2.1/2.2	1
	13	50	3	0.1	20	20	-10	140	FKM	444492W	7321BIV00	2.0/2.1/2.2	1
1/2"	13	50	3	0.1	20	20	-10	90	NBR	443779W	7321BAN00	2.0/2.1/2.2	1
	13	50	3	0.1	20	20	-10	90	NBR	443780W ₂	7321BAN01	2.0/2.1/2.2	1
	13	50	3	0.1	10	10	-10	140	EPDM	443781W ₁	7321BAH00	2.0/2.1/2.2	1
	13	50	3	0.1	20	20	-10	140	FKM	444494W	7321BAV00	2.0/2.1/2.2	1
3/4"	20	140	8.4	0.1	20	20	-10	90	NBR	443782W	7321BCN00	2.0/2.1/2.2	2
	20	140	8.4	0.1	10	10	-10	90	NBR	443783W ₂	7321BCN01	2.0/2.1/2.2	2
	20	140	8.4	0.1	10	10	-10	140	EPDM	443785W ₁	7321BCH00	2.0/2.1/2.2	2
	20	140	8.4	0.1	20	20	-10	140	FKM	444497W	7321BCV00	2.0/2.1/2.2	2
1"	25	160	9.6	0.1	20	20	-10	90	NBR	443786W	7321BDN00	2.0/2.1/2.2	2
	25	160	9.6	0.1	10	10	-10	90	NBR	443787W ₂	7321BDN01	2.0/2.1/2.2	2
	25	160	9.6	0.1	10	10	-10	140	EPDM	443789W ₁	7321BDH00	2.0/2.1/2.2	2
	25	160	9.6	0.1	20	20	-10	140	FKM	443804W	7321BDV00	2.0/2.1/2.2	2
1 1/4"	35	420	25.2	0.1	10	10	-10	140	EPDM	443793W ₁	7321BEH00	2.0/2.1/2.2	3
	35	420	25.2	0.1	10	10	-10	90	NBR	443790W	7321BEN00	2.0/2.1/2.2	3
	35	420	25.2	0.1	5	5	-10	90	NBR	443791W ₂	7321BEN01	2.0/2.1/2.2	3
1 1/2"	40	500	30	0.1	10	10	-10	140	EPDM	443797W ₁	7321BFH00	2.0/2.1/2.2	3
	40	500	30	0.1	10	10	-10	90	NBR	443794W	7321BFN00	2.0/2.1/2.2	3
	40	500	30	0.1	5	5	-10	90	NBR	443795W ₂	7321BFN01	2.0/2.1/2.2	3
2"	50	620	37.2	0.1	10	10	-10	140	EPDM	443801W ₁	7321BGH00	2.0/2.1/2.2	3
	50	620	37.2	0.1	10	10	-10	90	NBR	443798W	7321BGN00	2.0/2.1/2.2	3
	50	620	37.2	0.1	5	5	-10	90	NBR	443799W ₂	7321BGN01	2.0/2.1/2.2	3

Notes:

- Maximum pressure for steam: 4 bar (140 °C)
- With manual override