

TECHNICAL DATASHEET

Update : 26/02/2019

UNF TAP - SPIRAL FLUTE- HSSE 3% VANADIUM - MULTI-MATERIAL



Description

UNF thread . Blind hole taps



Characteristics

Ref.	EAN	Threading (inch)	Threading diameter (inch)	No. of threads per inch	Angle of helix °	Total length mm	Body material	Tolerance	Drilling diameter mm	Tail diameter mm	Square drive adapter mm
865004	3660338194382	UNF	8	36	40	63	HSSE 3% Vanadium	2B	3,5	2,8	2,1
865005	3660338194399	UNF	10	32	40	70	HSSE 3% Vanadium	2B	4	3,5	2,7
865003	3660338194375	UNF	6	40	40	56	HSSE 3% Vanadium	2B	2,95	2,5	2,1
865006	3660338194405	UNF	12	28	40	80	HSSE 3% Vanadium	2B	4,6	4	3
865007	3660338194412	UNF	1/4	28	40	80	HSSE 3% Vanadium	2B	5,4	4,5	3,4
865008	3660338194429	UNF	5/16	24	40	90	HSSE 3% Vanadium	2B	6,9	6	4,9
865002	3660338194368	UNF	5	44	40	56	HSSE 3% Vanadium	2B	2,6	2,2	
865009	3660338194436	UNF	3/8	24	40	90	HSSE 3% Vanadium	2B	8,4	7	5,5
865010	3660338194443	UNF	7/16	20	40	100	HSSE 3% Vanadium	2B	9,9	8	6,2
865011	3660338194450	UNF	1/2	20	40	100	HSSE 3% Vanadium	2B	11,5	9	7
865012	3660338194467	UNF	9/16	18	40	100	HSSE 3% Vanadium	2B	13	11	9
865013	3660338194474	UNF	5/8	18	40	100	HSSE 3% Vanadium	2B	14,5	12	9
865014	3660338194481	UNF	3/4	16	40	110	HSSE 3% Vanadium	2B	17,5	14	11
865015	3660338194498	UNF	7/8	14	40	125	HSSE 3% Vanadium	2B	20,4	18	14,5
865016	3660338194504	UNF	1	12	40	140	HSSE 3% Vanadium	2B	23,25	18	14,5
867027	3660338210648		4		40	56				3,5	2,7