



Single Yoke


* 3/4 = 6.18 (157)

1/4	Y64A-2AA-N1N
3/8	Y64A-3AA-N1N
1/2	Y64A-4AA-N1N
3/4	Y64A-6AA-N1N


Double Yoke

* 3/4 = 9.33 (237)


1/4	Y64A-2AA-N2N
3/8	Y64A-3AA-N2N
1/2	Y64A-4AA-N2N
3/4	Y64A-6AA-N2N

Yoke Connector

74503-51


Porting Block

- (2) 1/4 outlets
- (1) 3/8 outlet




P_1 max. = 250 psi (17 bar)
 T max. = 175°F (80°C)

74507-52 PTF
 74507-50 ISO G

Adjustable Pressure Switch


- 30-150 psi (2-10 bar) adjustable
- Porting block mounted
- DIN 43650 form C connector




P_1 max. = 250 psi (17 bar)
 T max. = 175°F (80°C)
 I max. = 5 A
 V max. = 240 V
 Reset differential
 = 15 psi (1 bar) nominal



4346-99

End Connector

- For use with end mounted porting block
- 1/2 or 3/4 over porting



1/2	74505-52 PTF
3/4	74505-55 PTF
1/2	74505-50 ISO G
3/4	74505-53 ISO G