

TECHNICAL DATASHEET

Update : 26/02/2019

SINGLE CIRCULAR BANJO COUPLER 2 PORTS

GISS

Description

Pressure: 15 bars . Operating temperature: -20 to +80°C . Industrial vacuum -100 kpa . NBR Seal. . H
Polymer and nickel-plated brass body



Characteristics

Ref.	EAN	Exterior tube diameter mm	Connecting diameter "	Execution	Material	Temperature area °C
859815	3660338147876	4	G1/8	Cylindrical	Body in H polymer/ nickel-plated brass	-20/+80
859816	3660338147883	4	G1/4	Cylindrical	Body in H polymer/ nickel-plated brass	-20/+80
859817	3660338147890	6	G1/8	Cylindrical	Body in H polymer/ nickel-plated brass	-20/+80
859818	3660338147906	6	G1/4	Cylindrical	Body in H polymer/ nickel-plated brass	-20/+80
859819	3660338147913	8	G1/8	Cylindrical	Body in H polymer/ nickel-plated brass	-20/+80
859820	3660338147920	8	G1/4	Cylindrical	Body in H polymer/ nickel-plated brass	-20/+80
859821	3660338147937	8	G3/8	Cylindrical	Body in H polymer/ nickel-plated brass	-20/+80
859822	3660338147944	10	G1/4	Cylindrical	Body in H polymer/ nickel-plated brass	-20/+80
859823	3660338147951	10	G3/8	Cylindrical	Body in H polymer/ nickel-plated brass	-20/+80
859824	3660338147968	10	G1/2	Cylindrical	Body in H polymer/ nickel-plated brass	-20/+80
859825	3660338147975	12	G1/4	Cylindrical	Body in H polymer/ nickel-plated brass	-20/+80
859826	3660338147982	12	G3/8	Cylindrical	Body in H polymer/ nickel-plated brass	-20/+80
859827	3660338147999	12	G1/2	Cylindrical	Body in H polymer/ nickel-plated brass	-20/+80