



Technical datasheet

4T-6386/6320

Single row tapered roller bearings

Tapered roller bearing, pressed steel cage

Visual(s)



Product definition

d	66.68 mm
D	135.76 mm
B	56.01 mm
C	44.45 mm
T	53.98 mm
d1	98 mm
a	35.18 mm
e	0.32
Y2	1.85
Y0	1.02
Mass	3.64 kg
Brand	NTN

Product performance

Dynamic load, C	278 kN
Rating life coefficient, A2	1.4
Static load, C0	380 kN
Fatigue limit load, Cu	46.3 kN
Nlim (oil)	3,800 rpm
Nlim (grease)	2,900 rpm
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.42 Hz
Characteristic rolling element frequency, BSF	5.62 Hz
Characteristic outer ring frequency, BPF0	6.65 Hz
Characteristic inner ring frequency, BPFI	9.35 Hz

Abutment dimensions

ra max	4.3 mm
r1a max	3.3 mm

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

$F_a / F_r \leq e$		$F_a / F_r > e$	
X	Y	X	Y
1	0	0.4	Y2

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X_0	Y_0
0.5	Y0

If $P_0 \leq F_r$, then use $P_0 = F_r$

The values for e, Y2 and Y0 are shown in the above table