


Air Filter


AF20-A to AF40-A

JIS Symbol

Air Filter



Air Filter with Auto Drain



AF20-A



AF40-A

How to Order

AF **30** - **03** **BD** - **A**

① ② ③ ④ ⑤

- Option/Semi-standard: Select one each for a to f.
- Option/Semi-standard symbol: When more than one specification is required, indicate in alphanumeric order.
Example) AF30-03BD-CR-A

		Symbol	Description	1				
				Body size				
				20	30	40		
2	Thread type	Nil	Rc	●	●	●		
		N <small>Note 1)</small>	NPT	●	●	●		
		F <small>Note 2)</small>	G	●	●	●		
			+					
3	Port size	01	1/8	●	—	—		
		02	1/4	●	●	●		
		03	3/8	—	●	●		
		04	1/2	—	—	●		
		06	3/4	—	—	●		
			+					
4	Option	a	Mounting	Nil	Without mounting option	●	●	●
				B <small>Note 3)</small>	With bracket	●	●	●
			+					
		b	Float type auto drain	Nil	Without auto drain	●	●	●
				C <small>Note 4)</small>	N.C. (Normal close) Drain port is closed when pressure is not applied.	●	●	●
				D <small>Note 5)</small>	N.O. (Normal open) Drain port is open when pressure is not applied.	—	●	●
			+					
5	Semi-standard	c	Bowl <small>Note 6)</small>	Nil	Polycarbonate bowl	●	●	●
				C	With bowl guard	●	— <small>Note 7)</small>	— <small>Note 7)</small>
					+			
		d	Drain port	Nil	With drain cock	●	●	●
				J <small>Note 8)</small>	Drain guide1/8	●	—	—
					Drain guide1/4	—	●	●
			W	Drain cock with barb fitting (for ø6 x ø4 nylon tube)	—	●	●	
					+			
		e	Flow direction	Nil	Flow direction: Left to right	●	●	●
				R	Flow direction: Right to left	●	●	●
			+					
f	Pressure unit	Nil	Name plate and caution plate for bowl in imperial units: MPa	●	●	●		
		Z <small>Note 9)</small>	Name plate and caution plate for bowl in imperial units: psi, °F	○ <small>Note 10)</small>	○ <small>Note 10)</small>	○ <small>Note 10)</small>		

Note 1) Drain guide is NPT1/8 (applicable to the AF20-A) and NPT1/4 (applicable to the AF30-A to AF40-A).

The auto drain port comes with ø3/8" One-touch fitting (applicable to the AF30-A to AF40-A).

Note 2) Drain guide is G1/8 (applicable to the AF20-A) and G1/4 (applicable to the AF30-A to AF40-A).

Note 3) A bracket is not assembled and supplied loose at the time of shipment. Including 2 mounting screws.

Note 4) When pressure is not applied, condensate which does not start the auto drain mechanism will be left in the bowl. Releasing the residual condensate before ending operations for the day is recommended.

Note 5) If the compressor is small (0.75 kW, discharge flow is less than 100 L/min[ANR]), air leakage from the drain cock may occur during start of operations. N.C. type is recommended.

Note 6) Refer to Chemical data on page 32 for chemical resistance of the bowl.

Note 7) Standard material (polycarbonate)

Note 8) Without a valve function.

Note 9) For thread type: NPT. This product is for overseas use only according to the new Measurement Law.

(The SI unit type is provided for use in Japan.)

Note 10) ○: For thread type: NPT only