


ASCO™ Solenoid Valves

High pressure, brass or stainless steel bodies, 1/4" - 3/4"



2/2
Series
223

Features

- Rugged piston construction built to withstand pressure ratings to 1500 psi
- Angle body design for high flows
- Ideal for high-pressure water applications, such as car washes
- Mountable in any position



Standard Voltages

DC (=): 24V
AC (~): VC, EF/VCEF, Redhat II 110V/50Hz-120V/60Hz; 220V/50Hz-240V/60Hz
SC, NF 115V/50Hz; 120V/60 Hz; 230V/50Hz

Specifications

Pipe Size (in)	Orifice Size (mm)	Kv Flow Factor (m³/h)	Operating Pressure Differential (bar)							Max. Fluid Temp. °C		Prefix							No Prefix	Catalog Number	
			Min.	Max. AC			Max. DC														
				Air-Inert Gas	Water	Light Oil @ 300 SSU	Air-Inert Gas	Water	Light Oil @ 300 SSU	AC	DC	SC	VC	EF/VCEF ⁽¹⁾	NF/NFET	HB	Brass	Stainless Steel			
NC - Normally closed (Closed when de-energized)																					
3/8	8	1.3	0.7	52	52	52	28	28	28	93	65	-	-	●	-	-	●	8223G023	-		
1/2	10	2.7	1.7	103	103	103	34	34	34	93	65	-	●	●	-	●	●	8223G003	-		
1/2	9	2.7	1.8	100	100	100	35	35	35	90	90	-	-	-	●	-	-	-	B223A010		
1/2	10	2.7	1.7	103	103	103	34	34	34	93	65	●	●	●	-	●	●	-	8223G010		
3/4	19	6.7	1.8	50	50	50	20	20	20	90	90	-	-	-	●	-	-	B223B005	-		
3/4	19	6.7	1.7	52	52	52	31	31	31	93	65	●	-	-	-	-	●	8223G005	-		
3/4	19	6.7	1.8	50	50	50	20	20	20	90	90	-	-	-	●	-	-	-	B223A012		
3/4	19	6.7	1.7	52	52	52	31	31	31	93	65	-	-	●	-	-	●	-	8223G012		

● Available Express

(1) Please refer to the page about "TECHNICAL INFORMATION - VCEF&VCEV Installation"