



## Take-up housing units RTUEY65-214-XL (Series RTUEY)

cast iron housing, radial insert ball bearing with grub screws in inner ring,  
R seals

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue ordering system ([https://www.schaeffler.de/content.schaeffler.de/en/news\\_media/index.jsp](https://www.schaeffler.de/content.schaeffler.de/en/news_media/index.jsp)) or by telephone on +49 (91 32) 82 - 28 97.

d	65 mm
L	214 mm
H	166 mm
A	70 mm
A <sub>1</sub>	25 mm Tolerance: H13
A <sub>2</sub>	50 mm
B	74,6 mm
H <sub>1</sub>	151 mm Tolerance: +/-0,25
L <sub>1</sub>	135 mm
L <sub>2</sub>	20 mm
L <sub>3</sub>	120 mm

N	41 mm	
N <sub>1</sub>	35 mm	
N <sub>2</sub>	70 mm	
Q	M6	
S <sub>1</sub>	44,4 mm	
T	110 mm	
m	7 kg	Mass
C <sub>r</sub>	66000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	44000 N	Basic static load rating, radial
	TUE13/14	Designation of housing
	GYE65-214-XL-KRR-B	Designation of bearing
	Alternative ball set 6214.	

