

Type : 3EL090L6C-PD-A0-C34

RE: 891571

Date : 03.01.2022

Power [kW]	: 1.10	Efficiency Class	: IE3
Input Voltage [V]	: 400	Duty Cycle	: S1
Connection Type [Δ / Y]	: Y	Service Factor	: 1.20
Frequency [Hz]	: 50	Frame Size	: 090L
Pole Number	: 6	Weight [kg]	: 17.0
Nominal Speed [rpm]	: 940	Insulation Class	: F [155°C]
Nominal Current [A]	: 2.75	Temperature Rise	: B [80°K]
Nominal Moment [Nm]	: 11.2	Protection Class	: IP55
Nominal Efficiency [η]	: 81.0	Vibration Severity Grade	: A
Power Factor [$\cos\phi$]	: 0.71	Method of Cooling	: IC411
Locked Rotor Current [I_a/I_n]	: 5.0	Direction of Rotation	: Bidirectional
Locked Rotor Torque [Ma/Mn]	: 2.2	Balance	: Half Key
Breakdown Torque [Mk/Mn]	: 2.7	Motor Protection	: --
Motor Color	: RAL 7031	Altitude Above Sea Level	: 1000m
Ambient Temperature	: -15°C / +40°C	Sound Pressure Level [dBA]	: 46

ELECTRICAL DATA

Δ / Y	U [V]	f [Hz]	P [kW]	n [rpm]	I [A]	η [%]	$\cos\phi$
Δ	230	50	1.10	940	4.76	81.0	0.71
Y	400	50	1.10	940	2.75	81.0	0.71
Y	460	60	1.28	1140	2.71	82.1	0.72


MECHANICAL DATA

Moment of Inertia [kgm ²]	: 0.00428
Bearing DS / NS	: 6205ZZ / 6205ZZ
Frame Material	: Aluminum
Flange Type / Material	: B3 / Aluminum
Cooling Fan Material	: Plastic
End Shield Material	: Aluminum

TERMINAL BOX

Terminal Box Material	: Aluminum
Terminal Box Position	: Top
Terminal Box Cable Entry	: M20x1.5
Terminal Box Blind Cap	: M16x1.5
Contact Screw Thread	: M4

MECHANICAL DIMENSIONS



FLANGE TYPE	D	E	L	AC	H	HE	HD	F	GA	DB	C	ϕK	B	BB	HA	AA	A	AB
B3	24	50	325	176	90	132	222	8	27	M8	56	10	125	151	4	27	140	167

Manufactured and tested in accordance with IEC 60034

*Technical data are subject to change! There may be discrepancies between calculated and rating plate values.

*MECALINE has right to change all the data without prior notice.

FR.AG.010 REV. NO: 03 REV TARİHİ : 01.01.2021

Europe
Rubix Engineering
61 Avenue Tony Garnier
69007 Lyon
France

UK
Brammer UK Ltd (A Rubix Company)
Dakota House, Concord Business Park
Manchester M22 0RR
UK