

SPECTACLES G-SNIPER (2 IN 1)

Item #	EAN	Product
854320	3660338101199	Clear
854321	3660338101205	Smoke

Description

Standard : EN 166 - EN 170 - EN 172 (smoked version).
Ultra comfortable and technical, modular glasses. Superior protection due to the foam present on the frame. Removable, adjustable braid. Non-slip nose

Applications Ideal for all mechanical hazards or activities in movement. Grinding, industry, sport, laboratories, assembly shops.

Characteristics

- Anti-mist and scratch resistant treatments.
- Supplied with a microfibre case.
- Weight: 30 g. legs version / 32 g. braided version.
- Extremely lightweight and modern safety eyewear.
- Outstanding field of vision and exceptional protection.
- Molded-in nose bridge provides uncompromised comfort and fit.
- Single-piece lens that will fit most faces.
- ISO9001 manufacturing ensuring a reliable and durable quality.
- As protection against mechanical risks: projections of solids, of chips, particles, shocks ...
- Protection against UV rays.



Instructions & storage

Check carefully that the equipment is suitable for the intended use.
Replace the used or deteriorated products.
Read the user information sheet enclosed with the product before use.

Standards and certifications

UK
CA

EN166: 2001, EN170: 2002. / EN172 (version fumée) Lens markings : 2C – 1.2 G 1 FT

Lens markings (smoke) : 5-2.5 G 1FT
Frame marking : CE EN166 FT

Mechanical protection	Symbole FT	Impact resistant against high speed particles at high temperatures (corresponds to the impact of a steel ball with a diameter of 6 mm and a minimum mass of 0.86 g launched at 45 m/s).
Optical quality	Symbole 1	Class 1 continuous works (better quality).
Scale number	Symbole 2C – 1.2 Smoke 5-2.5	Colour perception: may be impaired unless marked «2C». Typical application: for use with sources which emit predominantly ultraviolet radiation at wavelengths shorter than 313 nm and when glare is not an important factor: this covers the UVC and most of the UVD Bands (b). Typical sources: Low pressure mercury lamps such as lamps used to stimulate fluorescence or «black lights», mercury lamps, germicidal lamps. (b) U.V.B: 280 nm to 315 nm et U.V.C: 100 nm to 280 nm.

Packaging

- Carton of 200 units/ Box of 10 units/ Each unit individually packaged.