

TECHNICAL DATASHEET

Update : 26/02/2019

SINGLE CIRCULAR BANJO COUPLER 3 PORTS

GISS

Description

Pressure: 15 bars . Operating temperature: -20 to +80°C . Industrial vacuum -100 kpa . NBR Seal. . H
Polymer and nickel-plated brass body



Characteristics

Ref.	EAN	Exterior tube diameter mm	Connecting diameter "	Execution	Material	Temperature area °C
859829	3660338148002	4	G1/8	Cylindrical	Body in H polymer/ nickel-plated brass	-20/+80
859830	3660338148019	4	G1/4	Cylindrical	Body in H polymer/ nickel-plated brass	-20/+80
859831	3660338148026	6	G1/8	Cylindrical	Body in H polymer/ nickel-plated brass	-20/+80
859832	3660338148033	6	G1/4	Cylindrical	Body in H polymer/ nickel-plated brass	-20/+80
859833	3660338148040	8	G1/8	Cylindrical	Body in H polymer/ nickel-plated brass	-20/+80
859834	3660338148057	8	G1/4	Cylindrical	Body in H polymer/ nickel-plated brass	-20/+80
859835	3660338148064	8	G3/8	Cylindrical	Body in H polymer/ nickel-plated brass	-20/+80
859836	3660338148071	10	G1/4	Cylindrical	Body in H polymer/ nickel-plated brass	-20/+80
859837	3660338148088	10	G3/8	Cylindrical	Body in H polymer/ nickel-plated brass	-20/+80
859838	3660338148095	10	G1/2	Cylindrical	Body in H polymer/ nickel-plated brass	-20/+80
859839	3660338148101	12	G1/4	Cylindrical	Body in H polymer/ nickel-plated brass	-20/+80
859840	3660338148118	12	G3/8	Cylindrical	Body in H polymer/ nickel-plated brass	-20/+80
859841	3660338148125	12	G1/2	Cylindrical	Body in H polymer/ nickel-plated brass	-20/+80