

BOLT CUTTERS

Description

- Blades in chromium-molybdenum steel for greater robustness
 - Blades hardness HRC 40-50 / Cutting edge HRC 60-65
 - High frequency heat treatment of the cutting edge to improve the hardness
- Axial cut
- Adjustment bolt for quick and easy adjustment of the blades
- Tubular arms for greater lightness and less fatigue during extended use
- Ergonomic handles with grip for greater comfort
- Replacement jaws available for greater durability (896080 = replacement jaws for 896076 / 896081 = replacement jaws for 896077 / 896082 = replacement jaws for 896078 / 896083 = replacement jaws for 896079)
- Professional quality: we rigorously test all our ROEBUCK products to the highest industry standards and offer a lifetime warranty covering repair or replacement of tools

Technical Specifications

REF	EAN	Products	Dimensions	Cutting capacity	Weight
896076	3660338483820	450mm/18"	460 x 33.5 x 110 mm	19HRC - ø 8mm 40HRC - ø 6.5mm 48HRC - ø 6mm	1500 g
896077	3660338483837	600mm/24"	620 x 38.5 x 140 mm	19HRC - ø 9.5mm 40HRC - ø 8mm 48HRC - ø 7mm	2540 g
896078	3660338483844	750mm/30"	780 x 45 x 155 mm	19HRC - ø 11mm 40HRC - ø 9mm 48HRC - ø 8mm	3890 g
896079	3660338483851	900mm/36"	890 x 49.5 x 175 mm	19HRC - ø 13mm 40HRC - ø 11mm 48HRC - ø 9mm	5670 g

