

## Self Amalgamating Tape

**F4P®**

For extruding power cables up to Um 72kV, both buried and aerial.  
For indoor and outdoor applications.

ref: **SAT9**

- Excellent conformability  
- easily compressed and moulded by hand
- Will not corrode copper
- Dielectric strength 16kV/mm
- Roll size: 25mm x 10 metres



## Cable Warning Tape

**F4P®**

A non-adhesive, heavy gauge polyethylene tape printed with a warning text to identify to future excavators the potential danger of the cable below.

ref: **CWT**

- Reads "CAUTION ELECTRIC CABLE BELOW"
- Resistant to acids and alkalines
- Colour: Yellow tape with black print
- Roll size: 150mm x 365 metres



CAUTION CAUTION CAUTION CAUTION CAUTION CAUTION CAUTION CAUTION  
ELECTRIC CABLE BELOW ELECTRIC CABLE BELOW ELECTRIC CABLE

## Earth Clamps

**F4P®**

Designed to BS 951:1986, made from zinc treated copper or phosphor bronze and supplied with appropriate coloured safety label.

These earth clamps are colour coded:

- **RED** to indicate use in dry areas (Copper)
- **BLUE** for corrosive conditions (Phosphor bronze)
- **GREEN** to be used in humid conditions (Phosphor bronze)



ref	terminal rating	maximum earth area	pipe diameter	overall length	colour code	pack qty
<b>TEC14</b>	2.5 - 10mm <sup>2</sup>	1 x 10mm <sup>2</sup>	12 - 32mm	135mm	Red	20
<b>TEC15</b>	2.5 - 10mm <sup>2</sup>	1 x 10mm <sup>2</sup>	12 - 32mm	135mm	Blue	20
<b>TEC16</b>	2.5 - 16mm <sup>2</sup>	2 x 10mm <sup>2</sup>	12 - 32mm	135mm	Green	20

## Heat Shrink Sleeving

**F4P®**

Suitable for the electrical insulation and bonding of cables and connectors, as well as corrosion-proofing metallic rods, tubes and aerials.

- Minimum 2:1 shrink ratio
- Shrink temperature: 90°C
- Approved to UL 224 VW-1
- Pack contents:
  - 3 x black sleeves
  - 3 x blue sleeves
  - 3 x brown sleeves
  - 3 x grey sleeves
  - 3 x green/yellow sleeves



ref	description	sleeve length
<b>F4PHSP4824</b>	Ø4.8 - 2.4mm sleeving pack	190mm
<b>F4PHSP7030</b>	Ø7.0 - 3.0mm sleeving pack	190mm
<b>F4PHSP10050</b>	Ø10.0 - 5.0mm sleeving pack	190mm
<b>F4PHSP190100</b>	Ø19.0 - 10mm sleeving pack	190mm

## Galvanised Steel Banding

**F4P®**

Pre-punched steel banding ideal for fixing, supporting joists and general construction.

- Highly versatile multi-purpose fixing band
- Easy to cut and bend
- Pre-punched Ø5mm hole pattern for easy fixing using nails, screws or bolts
- 0.8mm thickness
- 12mm and 17mm width options
- Available as plain finish, or with black PVC coating

### Standard Steel Banding



ref: **F4PGSB12**  
10 metre coil, Ø12mm

ref: **F4PGSB17**  
10 metre coil, Ø17mm

### PVC Coated Steel Banding



ref: **F4PGSB12PVC**  
10 metre coil, Ø12mm

ref: **F4PGSB17PVC**  
10 metre coil, Ø17mm

## Self Adhesive Cable Clips

**F4P®**

- Galvanised mild steel
- Use where holes are not a viable choice
- Adheres to many clean flat surfaces (steel, UPVC, aluminium, glass, RSJs, racking, single skin structures, etc).



ref	dimensions	max cable	pack qty
<b>SAFMINI</b>	14 x 30mm	Ø3mm	100
<b>SAF1</b>	20 x 30mm	Ø4mm	100
<b>SAF2</b>	25 x 37mm	Ø8mm	100
<b>SAF3</b>	32 x 44mm	Ø12mm	100
<b>SAF4</b>	38 x 53mm	Ø16mm	100