

Cable Ties

Nylon Cable Ties

Crimp-Pak Cable Ties are produced to comply with BS EN50146:2000 requirements and are supplied in accordance with ISO 9001 accreditation. All have an operating temperature range of -40°C to +85°C and are primarily manufactured from virgin nylon 66.

Specification:

Material: High quality virgin nylon 66 halogen free

Strength: Tensile strength to UL Specification

Operating Temperature: -40°C - +85°C

Flame Resistance: UL94V2

UL: Approved

Pack Qty: 100 (approx)

Black Cable Ties



code	size (mm)	max. bundle	min. tensile strength	pack quantity
650002	100 x 2.5	22	8 kg	100
650004	140 x 3.6	33	18 kg	100
650005	160 x 2.5	40	8 kg	100
650006	160 x 4.8	38	22 kg	100
650007	200 x 2.5	53	8 kg	100
650008	200 x 3.6	53	18 kg	100
650009	200 x 4.8	50	22 kg	100
650010	300 x 3.6	76	18 kg	100
650011	300 x 4.8	76	22 kg	100
650012	300 x 7.6	76	55 kg	100
650013	370 x 4.8	102	22 kg	100
650014	370 x 7.6	102	55 kg	100
650015	450 x 9.0	120	80 kg	100
650016	526 x 9.0	160	80 kg	100
650026	580 x 12.6	152	114 kg	100
650020	610 x 9.0	187	80 kg	100
650017	776 x 9.0	228	80 kg	100
650022	1020 x 9.0	295	80 kg	100

Natural Cable Ties



code	size (mm)	max. bundle	min. tensile strength	pack quantity
651001	80 x 2.4	15	8 kg	100
651020	100 x 2.4	22	8 kg	100
651002	100 x 2.5	33	18 kg	100
651004	140 x 3.6	40	8 kg	100
651005	160 x 2.5	38	22 kg	100
651006	160 x 4.8	53	8 kg	100
651007	200 x 2.5	53	18 kg	100
651008	200 x 3.6	50	22 kg	100
651009	200 x 4.8	76	18 kg	100
651010	300 x 3.6	76	22 kg	100
651011	300 x 4.8	76	55 kg	100
651012	300 x 7.6	102	22 kg	100
651013	370 x 4.8	102	55 kg	100
651014	370 x 7.6	120	80 kg	100
651015	450 x 9.0	140	80 kg	100
651016	526 x 9.0	152	114 kg	100
651026	650 x 9.0	228	80 kg	100
651017	776 x 9.0	295	80 kg	100
651022	940 x 9.0	295	80 kg	100