



## **Faster, Safer & Cleaner**

Abrasive cutting can create excessive dust, fumes, smoke, fire and can even explode. Evolution® TCT saws cut steel quickly, producing no heat and virtually no sparks, creating a much safer working environment. The cut is consistently clean and burr free, meaning less time is spent finishing the material after the cut.

# **3 Year Warranty**

All Evolution® Steel range saws come with a 3 year limited warranty. Designed with performance and versatility in mind and tested to the highest standards of reliability and durability. So although you're covered by our warranty, it's possible you'll never need it.

## **Full Specialist Blade Range Available**

The economy and high performance of an Evolution® blade stretches beyond the ability to cut steel cold. Evolution's specialist blade range also enables you to cut steel, stainless steel, aluminum and wood with the optional blades available.





## **BLADE RANGE**



#### STEEL

Designed specifically to cut steel. Material applications include: Square tube, angle iron, mild steel plate, pipe, tube & other ferrous metals. (HB 200-220)



#### STAINLESS STEEL

Designed specifically to cut 302, 303 & 304 grades of Stainless Steel only. Material applications include: square tube, angle iron, stainless steel plate, diamond plate, pipe & tube.



#### ALUMINIUM

Designed specifically to cut Aluminum & other non-ferrous metals. Material applications include: grating, extrusions, pipe & tube.



### THIN STEEL

Designed specifically to cut Wood. The high grade carbide tooth configuration enables fast efficient cutting & increased durability.

Designed specifically to cut Thin Steel. Ideal for cutting ferrous metal under 3mm thickness, Material applications include: sheet metal, metal roofing and electrical conduit.

ТҮРЕ	CODE	SIZE	RPM	BORE	KERF	TEETH
STEEL	EVOBLADE	180mm	3900	20mm	2mm	36
STAINLESS STEEL	EVOBLADESS	180mm	3900	20mm	1.8mm	48
ALUMINIUM	EVOBLADEAL	180mm	3900	20mm	2mm	54
WOOD	EVOBLADEWD	180mm	3900	20mm	2.2mm	30
THIN STEEL	EVOBLADETS	180mm	3900	20mm	1.6mm	68
STEEL	EVOBLADE230	230mm	3000	25.4mm	2mm	48
STAINLESS STEEL	EVOBLADE230SS	230mm	3000	25.4mm	1.8mm	60
ALUMINIUM	EVOBLADE230AL	230mm	3000	25.4mm	2.4mm	80
WOOD	EVOBLADE230WD	230mm	3000	25.4mm	2.4mm	40
STEEL	EVOBLADE255	255mm	5200	25.4mm	2mm	52
STEEL	66TBLADE	355mm	1600	25.4mm	2.4mm	66
STAINLESS STEEL	90TBLADE	355mm	1600	25.4mm	2.4mm	90
ALUMINIUM	80TBLADE14	355mm	1600	25.4mm	2.4mm	80
THIN STEEL	EVOBLADE355TS	355mm	1600	25.4mm	2.4mm	90