


Two-bolt flanged housing units

Flake graphite cast iron housing
Oval version
With Corrotect coating



PCJT...XL-N-FA125,
RCJT...XL-N-FA125

Dimension table - Dimensions in mm								
Designation			Mass	Dimensions				
Unit	Housing ²⁾	Radial insert ball bearing	m ≈ kg	d	H	J	L	A
PCJT20-XL-N-FA125	CJT04	GRAE20-XL-NPP-B-FA125	0,45	20	112	90	61	28
RCJT20-XL-N-FA125	CJT04	GE20-XL-KRR-B-FA125	0,48	20	112	90	61	28
PCJT25-XL-N-FA125	CJT05	GRAE25-XL-NPP-B-FA125	0,58	25	124	99	70	26,5
RCJT25-XL-N-FA125	CJT05	GE25-XL-KRR-B-FA125	0,64	25	124	99	70	26,5
PCJT30-XL-N-FA125	CJT06	GRAE30-XL-NPP-B-FA125	0,84	30	142	116,5	80	29
RCJT30-XL-N-FA125	CJT06	GE30-XL-KRR-B-FA125	0,9	30	142	116,5	80	29
PCJT35-XL-N-FA125	CJT07	GRAE35-XL-NPP-B-FA125	1,18	35	155	130	92	30,5
RCJT35-XL-N-FA125	CJT07	GE35-XL-KRR-B-FA125	1,25	35	155	130	92	30,5
PCJT40-XL-N-FA125	CJT08	GRAE40-XL-NPP-B-FA125	1,57	40	172	143,5	105	34,5
RCJT40-XL-N-FA125	CJT08	GE40-XL-KRR-B-FA125	1,68	40	172	143,5	105	34,5
PCJT50-XL-N-FA125	CJT10	GRAE50-XL-NPP-B-FA125	1,98	50	190	157	116	39
RCJT50-XL-N-FA125	CJT10	GE50-XL-KRR-B-FA125	2,2	50	190	157	116	39
PCJT60-XL-N-FA125	CJT12	GRAE60-XL-NPP-B-FA125	3,37	60	238	202	138	46

- 1) To be ordered separately.
For a description of the end caps, see page 386.
- 2) The housings have the Corrotect coating.
- 3) Lubrication nipple M6 fitted.