














































Series M3, R 1/8

Series	Model	Description	Application	Note
M3	M-3AU-3	Barb fitting for soft tube 	For soft nylon tubing For polyurethane tubing	ø3.18/2.18 x M3 ø3.18/2 x M3
	M-3AU-4	 P.150	For soft nylon and polyurethane tubing	ø4/2.5 x M3
	M-3ALU-3	Barb elbow for soft tubing 	For soft nylon tubing Body rotates at 360° around the stud axis	ø3.18/2.18 x M3 ø3.18/2 x M3
	M-3ALU-4	 P.150	For soft nylon and polyurethane tubing	ø4/2.5 x M3
	M-3SUL	Universal elbow 	Body rotates at 360° around the stud axis	M3 female x M3 male
	M-3UT	Universal tee 	Body rotates at 360° around the stud axis	M3 female x M3 female x M3 male
	M-3N	Nipple 	Fitting to workpiece and fitting to fitting connection	M3 male x M3 male
	M-3P	Plug 	Use to plug unused M3 port	
		P.150		

Series	Model	Description	Application	Note
R 1/8	M-01AN-4	Barb fitting for nylon tubing 	For nylon tubing	ø4/2.5 x R 1/8
	M-01AN-6	 P.150		ø6/4 x R 1/8
	M-01AU-4	Barb fitting for soft tubing 	For soft nylon and polyurethane tubing	ø4/2.5 x R 1/8
	M-01AU-6	 P.150		ø6/4 x R 1/8
	M-01H-4	Hose nipple 	For nylon, soft nylon and polyurethane tubing	ø4/2.5 x R 1/8
	M-01H-6	 P.150		ø6/4 x R 1/8

Series M5

Series	Model	Description	Application	Note
M5	M-5AN-4	Barb fitting for nylon tubing 	For nylon tubing	ø4/2.5 x M5
	M-5AN-6	 P.151		ø6/4 x M5
	M-5AU-3	Barb fitting for soft tubing 	For soft nylon tubing For polyurethane tubing	ø3.18/2.18 x M5 ø3.18/2 x M5
	M-5AU-4	 P.151	For soft nylon and polyurethane tubing	ø4/2.5 x M5 ø6/4 x M5
	M-5ALN-4	Barb elbow for nylon tubing 	• For nylon • Body rotates at 360° around the stud axis	ø4/2.5 x M5 ø6/4 x M5
	M-5ALN-6	 P.151		
	M-5ALU-3	Barb elbow for soft tubing 	For soft nylon tubing Body rotates at 360° around the stud axis	ø3.18/2.18 x M5 ø3.18/2 x M5
	M-5ALU-4	 P.151	For soft nylon and polyurethane tubing	ø4/2.5 x M5 ø6/4 x M5
	M-5ALHN-4	Barb elbow (H) for nylon tubing 	Body rotates at 360° around the stud axis For nylon tubing	ø4/2.5 x M5 ø6/4 x M5
	M-5ALHN-6	 P.151		
M5	M-5ALHU-3	Barb elbow (H) for soft tubing 	For soft nylon tubing Body rotates at 360° around the stud axis	ø3.18/2.18 x M5 ø3.18/2 x M5
	M-5ALHU-4	 P.151	For polyurethane tubing For soft nylon and polyurethane tubing	ø4/2.5 x M5 ø6/4 x M5
	M-5ALHU-6	 P.151		
	M-5H-4	Hose nipple 	For nylon, soft nylon and polyurethane tubing	ø4/2.5 x M5 ø6/4 x M5
	M-5H-6	 P.151		
	M-5HL-4	Hose elbow 	• For nylon, soft nylon and polyurethane tubing • Body rotates at 360° around the stud axis	ø4/2.5 x M5 ø6/4 x M5
	M-5HL-6	 P.152		
	M-5HLH-4	Hose elbow (H) 	Body rotates at 360° around the stud axis	ø4/2.5 x M5 ø6/4 x M5
	M-5HLH-6	 P.152		
	M-5L	Elbow 	One-sided 90° elbow	M5 female x M5 female

Series	Model	Description	Application	Note
M5	M-5T	tee 	Both sides allow 90° connection	M5 female x M5 female
	M-5UL	Universal elbow 	Body rotates at 360° around the stud axis	M5 female x M5 male
	M-5UT	Universal tee 	Body rotates at 360° around the stud axis	M5 female x M5 female x M5 male
	M-5J	Extension fitting 	Solid piece moves fitting up from workpiece	M5 male x M5 female
	M-5N	Nipple 	Fitting to workpiece and fitting to fitting connection	M5 male x M5 male
	M-5UN	Universal nipple 	Body rotates at 360° around the stud axis	M5 male x M5 male PAT.
	M-5E	Bulkhead union 	Panel-mount connection	M5 female x M5 female
	M-5ER	Bulkhead reducer 	Reduction from Rc 1/8 to M5 including panel or bracket mounting	Rc 1/8 x M5 female
	M-5M	Manifold 	For reducing Rc 1/8 female be diverted to up to 9, M5 stations, including panel or bracket mounting	Rc 1/8 x M5 female (9 stations)
	M-5B	Bushing 	For reducing R 1/8 female to M5.	R 1/8 x M5 female
M5	M-5P	Plug 	Use to plug unused M5 port.	
		P.153		

KQ2

KQB2

KS
KX

KM

KF

M

H/DL
L/LL

KC

KK

KK130

DM

KDM

KB

KR

KA

KQG2

KG

KFG2

MS

KKA

KP

LQ


MQR

T


Series M

Series M3


Barb Fitting for Soft Tubing: M-3AU-3




Barb Fitting for Soft Tubing: M-3AU-4




Barb Elbow for Soft Tubing: M-3ALU-3




Barb Elbow for Soft Tubing: M-3ALU-4




Universal Elbow: M-3UL




Universal Tee: M-3UT



Nipple: M-3N




Plug: M-3P



Series R 1/8

Barb Fitting for Nylon Tubing, Soft Tubing: M-01A□-4/-6

Applicable tubing	Model	A	B	øC	Effective area (mm²)	Weight (g)
Nylon tubing	M-01AN-4	15.1	5	1.8	2.1	6.4
	M-01AN-6	17.1	7	2.5	4.0	6.6
Soft tubing	M-01AU-4	15.1	5	1.8	2.1	6.5
	M-01AU-6	17.1	7	2.5	4.0	6.7



Hose Nipple: M-01H-4/-6

Model	A	B	øC	øD	E	Effective area (mm²)	Weight (g)
M-01H-4	18.6	8.5	1.8	6.5	7	2.1	7.1
M-01H-6	19.6	9.5	3	8.5	8	5.5	7.7

