

### MASKING ADHESIVE TAPE 80°C

Article #	EAN	Product
<b>886630</b>	3660338400391	Masking tape: 24mm
<b>886631</b>	3660338400407	Masking tape: 48mm

#### Description

125 µm semi crepe tape coated with a solvent rubber adhesive system, recommended for all general purpose indoor 80°C masking applications. Continuous temperature resistance: +80°C. Resistant to oven baking. Resistant to chemicals, lacquers and solvents. No staining. Good shear and holding strength. Flexible and easy to use. Good peel adhesion. Excellent paint flake resistance. Smooth and controlled unwind. Clean and easy removal.



#### Applications

Suitable for all general purpose 80°C indoor bonding, holding, sealing and masking applications. Industrial OEM premium masking tape. Premium masking tape for building and painters masking applications for indoor use. Automotive aftermarket masking tape with short term oven baking resistance.

#### Characteristics

Colour	Width (mm)	Length (M)	Thickness (mm)	Max temp (°C)
CREAM	24.0	50.0	0.125	80.0
CREAM	48.0	50.0	0.125	80.0

#### Instructions & storage

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants. Masking tapes are not suitable for outdoor exposure and should not be submitted to prolonged periods of sunlight, as tapes may become difficult to remove. Clean removal may also vary with surface type, lacquers, primers and paints nature and the temperature of the surface at removal. For best results, remove the tape as soon as possible after applying the paints pulling it slowly at a 90° angle with constant speed. The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Storage temperature between +10°C and +30°C. Under these conditions, the storage life of the tape in a temperate climate will be at least one year.

#### Packaging

- Unit