

849117

REF.	849117
 LG. KG	2.5 m 140 KG
 CE	EN 360:2002
 MAT.	PVC PA & PES 50 mm
	Acier  STEEL
 360°	x1
R(kN)	15 kN
	NO
 Kg	1.20 KG



Longueur Poids maxi utilisateur
Length Max. user weight
Longitud Peso máximo del usuario
Lunghezza Peso Max. dell'utente
Länge Höchstgewicht des Benutzers
Lengte Max. Gebruikersgewicht



Matière carter / sangle
 Material of casing / webbing
Material cárter / correa
 Material dei carter / Cinghia
Material Gehäuse / Gurt
 Materiaal van omhulsel / band



Nombre d'émerillons
 Number of swivels
Cantidad de eslabones giratorios
 Numero di tornichetti
Anzahl der Wirbel
 Aantal wartels



Matière connecteur haut / connecteur bas
 Material of top connector / bottom connector
Material conector alto / conector bajo
 Materiale connettore alto / connettore basso
Material oberes / unteres Verbindungselement
 Materiaal bovenste connector / onderste connector



Homologué pour le travail à proximité d'arêtes vives
 Approved for work near sharp edges
Homologado para trabajo cerca de aristas vivas
 Omologato per lavoro in prossimità di spigoli vivi
Zugelassen für Arbeiten in der Nähe scharfer Kanten
 Goedgekeurd voor werk in de buurt van scherpe randen