

Solenoid coil VACC-S18-25-K5-3U-EX4D

Part number: 562902

FESTO



Data sheet

Feature	Value
Type code	VACC
Actuation type	Electrical
Mounting position	Any
Switching position indication	no
Duty cycle	100%
Insulation class	H
Coil characteristics	230 V AC: 40/65 Hz, power 2.5 VA 230 V DC: 2.5 W
Permissible voltage fluctuations	-15 % / +10 %
ATEX category gas	II 2G
Type of ignition protection for gas	Ex db IIC T6, T5, T4 Gb
ATEX category for dust	II 2D
Type of (ignition) protection for dust	Ex tb IIIC T85°C, T95°C, T130°C Db
Explosion protection certification outside the EU	EPL Db (CN) EPL Db (BR) EPL Db (IN) EPL Db (IEC-EX) EPL Gb (BR) EPL Db (KR) EPL Gb (CN) EPL Gb (IEC-EX) EPL Gb (IN) EPL Gb (KR)
Explosive ambient temperature	T4, T130°C: -50°C ≤ Ta ≤ +90°C T5, T95°C: -50°C ≤ Ta ≤ +55°C T6, T80°C: -50°C ≤ Ta ≤ +40°C
Certificate issuing authority	BVS15ATEXE135 IECEXBVS.15.0116 INMETRO DNV 17.0040X KGS 16-GA4BO-0896X PESO P396315 NEPSI GY17.1236X KGS 16-GA4BO-0897X

Feature	Value
Explosion prevention and protection	Zone 1 (BR) Zone 1 (ATEX) Zone 1 (CN) Zone 1 (IEC-EX) Zone 21 (BR) Zone 21 (ATEX) Zone 1 (KR) Zone 2 (ATEX) Zone 21 (CN) Zone 21 (IEC-EX) Zone 22 (ATEX) Zone 21 (KR)
CE marking (see declaration of conformity)	as per EU explosion protection directive (ATEX)
Corrosion resistance class (CRC)	4 - Particularly high corrosion stress
Degree of protection	IP65
Product weight	1700 g
Electrical connection	Terminal box, cable entry thread NPT1/2
Note on materials	RoHS-compliant Contains paint-wetting impairment substances
Solenoid coil material	Wrought aluminum alloy Gray cast iron