

Type : 4EL132S4D-FA-BA-C34

RE : 894227

Date : 03.01.2022

Power [kW]	: 5.50	Efficiency Class	: IE4
Input Voltage [V]	: 400	Duty Cycle	: S1
Connection Type [Δ / Y]	: Δ	Service Factor	: 1.25
Frequency [Hz]	: 50	Frame Size	: 132S
Pole Number	: 4	Weight [kg]	: 60
Nominal Speed [rpm]	: 1470	Insulation Class	: F [155°C]
Nominal Current [A]	: 11.1	Temperature Rise	: B [80°K]
Nominal Moment [Nm]	: 35.7	Protection Class	: IP55
Nominal Efficiency [η]	: 91.9	Vibration Severity Grade	: A
Power Factor [$\cos\phi$]	: 0.78	Method of Cooling	: IC411
Locked Rotor Current [I_a/I_n]	: 7.7	Direction of Rotation	: Bidirectional
Locked Rotor Torque [Ma/Mn]	: 3.8	Balance	: Half Key
Breakdown Torque [Mk/Mn]	: 3.7	Motor Protection	: PTC
Motor Color	: RAL 7031	Altitude Above Sea Level	: 1000m
Ambient Temperature	: -15°C / +40°C	Sound Pressure Level [dBA]	: 61

ELECTRICAL DATA

Δ / Y	U [V]	f [Hz]	P [kW]	n [rpm]	I [A]	η [%100]	η [%75]	η [%50]	$\cos\phi$	Cl
Δ	400	50	5.50	1470	11.1	91.9	91.8	90.6	0.78	IE4
Y	690	50	5.50	1470	6.41	91.9	91.8	90.6	0.78	IE4
Δ	460	60	6.38	1765	11.0	92.4	92.1	90.6	0.79	IE4


MECHANICAL DATA

Moment of Inertia [kgm ²]	: 0.03418
Bearing [DS / NS]	: 6208ZZ / 6208ZZ
Frame Material	: Aluminum
Flange Type / Material	: B5 / Aluminum
Cooling Fan Material	: Plastic
End Shield Material	: Aluminum

TERMINAL BOX

Terminal Box Material	: Aluminum
Terminal Box Position	: Top
Terminal Box Cable Entry	: M20x1.5+M25x1.5
Terminal Box Blind Cap	: --
Contact Screw Thread	: M5

MECHANICAL DIMENSIONS



FLANGE TYPE	D	E	N	P	T	LA	L	AC	S	M	H	HE	HD	F	GA	DB	C	ϕK	B	BB	HA	AA	A	AB
B5	38	80	230	300	4	20	495	257	14.5	265	132	181	313	10	41	M12	89	12	140	212	5	34	216	254

Manufactured and tested in accordance with IEC 60034

FR.AG.010 REV. NO: 04 REV TARİHİ : 01.01.2022

*Technical data are subject to change! There may be discrepancies between calculated and rating plate values.

Mecaline Motor has right to change all the data without prior notice.