

Type : 3EL132M6C-PD-BA-C34

RE: 891575

Date : 03.01.2022

Power [kW] : 4.00
 Input Voltage [V] : 400
 Connection Type [Δ / Y] : Δ
 Frequency [Hz] : 50
 Pole Number : 6
 Nominal Speed [rpm] : 970
 Nominal Current [A] : 8.52
 Nominal Moment [Nm] : 39.4
 Nominal Efficiency [η] : 86.8
 Power Factor [$\cos\phi$] : 0.78
 Locked Rotor Current [I_a/I_n] : 6.2
 Locked Rotor Torque [Ma/Mn] : 2.2
 Breakdown Torque [Mk/Mn] : 3.0
 Motor Color : RAL 7031
 Ambient Temperature : -15°C / +40°C

Efficiency Class : IE3
 Duty Cycle : S1
 Service Factor : 1.20
 Frame Size : 132M
 Weight [kg] : 51.0
 Insulation Class : F [155°C]
 Temperature Rise : B [80°K]
 Protection Class : IP55
 Vibration Severity Grade : A
 Method of Cooling : IC411
 Direction of Rotation : Bidirectional
 Balance : Half Key
 Motor Protection : PTC
 Altitude Above Sea Level : 1000m
 Sound Pressure Level [dBA] : 58

ELECTRICAL DATA

Δ / Y	U [V]	f [Hz]	P [kW]	n [rpm]	I [A]	η [%]	$\cos\phi$
Δ	400	50	4.00	970	8.52	86.8	0.78
Y	690	50	4.00	970	4.92	86.8	0.78
Δ	460	60	4.64	1170	8.43	87.5	0.79


MECHANICAL DATA

Moment of Inertia [kgm²] : 0.03493
 Bearing DS / NS : 6208ZZ / 6208ZZ
 Frame Material : Aluminum
 Flange Type / Material : B3 / Aluminum
 Cooling Fan Material : Plastic
 End Shield Material : Aluminum

TERMINAL BOX

Terminal Box Material : Aluminum
 Terminal Box Position : Top
 Terminal Box Cable Entry : M20x1.5+M25x1.5
 Terminal Box Blind Cap : --
 Contact Screw Thread : M5

MECHANICAL DIMENSIONS



FLANGE TYPE	D	E	L	AC	H	HE	HD	F	GA	DB	C	ϕK	B	BB	HA	AA	A	AB
B3	38	80	495	257	132	181	313	10	41	M12	89	12	178	212	5	34	216	254

Manufactured and tested in accordance with IEC 60034

*Technical data are subject to change! There may be discrepancies between calculated and rating plate values.

*MECALINE has right to change all the data without prior notice.

FR.AG.010 REV. NO: 03 REV TARİHİ : 01.01.2021

Europe
 Rubix Engineering
 61 Avenue Tony Garnier
 69007 Lyon
 France

UK
 Brammer UK Ltd (A Rubix Company)
 Dakota House, Concord Business Park
 Manchester M22 0RR
 UK