

TECHNICAL DATASHEET

Update: 27/07/2021

SPECTACLES G-MIRAGE			
Item #	EAN	Product	
840356	3660338056215	CLEAR	

Description

Protective polycarbonate glasses with trendy design. Extra flat, bi material side arms (polycarbonate and TPE). Weight: 25 g

Applications All types of industries, inside or outside, construction and building, medical or paramedical laboratory.



Characteristics

- Fine and flexible, they go well with any noise-protection system and helmet wearing.
- Perfect ergonomy, they offer a wide field of vision.
- Extremely lightweight and modern safety eyewear.
- Outstanding field of vision and exceptional protection.
- Molded-in nose bridge provides uncompromised comfort and fit.
- Single-piece lens that will fit most faces.
- ISO9001 manufacturing ensuring a reliable and durable quality.
- Type(s) of uses

As protection against mechanical risks: projections of solids, of chips, particles, shocks ... Grinding, industry, sport, laboratories, assembly shops.

Protection against UV rays.

Instructions & storage

Check carefully that the equipment is suitable for the intended use.

Replace the used or deteriorated products.

Read the user information sheet enclosed with the product before use.

Standards and certifications



Standard EN166 - EN170

Mechanical protection	Symbole FT	Impact resistant against high speed particles at high temperatures (corresponds to the impact of a steel ball with a diameter of 6 mm and a minimum mass of 0.86 g launched at 45 m/s).
Optical quality	Symbole 1	Class 1 continuous works (better quality).
Scale number	Symbole 2C.1.2	Colour perception: may be impaired unless marked «2C». Typical application: for use with sources which emit predominantly ultraviolet radiation at wavelengths shorter than 313 nm and when glare is not an important factor: this covers the UVC and most of the UVD Bands (b). Typical sources: Low pressure mercury lamps such as lamps used to stimulate fluorescence or «black lights», mercury lamps, germicidal lamps. (b) U.V.B: 280 nm to 315 nm et U.V.C: 100 nm to 280 nm.

Packaging

- Carton of 100 units/ box of 10 units/ each unit under individual polybag