

# EXTREME® STONE DRILLS

*Innovative shape of the HM plate allows precise drilling and thus longer durability*



## UNIQUE HM QUALITY

With low-stress high-temperature copper brazing for maximum durability and break-out prevention.



## 3 MILLED CLAMPING SURFACES

The clamping surfaces ensure a secure fit in the chuck and prevent spinning of the drill when drilling.



## HARDENED STEEL BODY

For optimal power transmission and breakage stability.

**FEATURES:** Heavy duty drilling hammer • Unique hard metal quality with low-stress high-temperature copper soldering - Optimized for maximum durability and break-out safety • Hardened steel body with core reinforcement and large-volume machined spiral - For maximum tensile strength combined with very high drilling progress • Shaft with three milled clamping surfaces - For a slip-proof stop.

**APPLICATIONS:** Main application area: assembly and fastening technology • Designed for use in impact drills and hammers with clamping chucks and max. 2.0 Joule impact energy for drilling in concrete, masonry, natural and artificial stone, bricks, tiles, etc.

*For use with drilling machines and drilling hammers (cordless and corded)*



Concrete



Brick



Steel

**EXTREME®**


## SINGLE PACKS

Article number	Diameter mm	Total length mm	Working length mm	Pack qty.
DT6695-XJ	3	110	70	1
DT6671-XJ	4	75	50	1
DT6672-XJ	5	85	50	1
DT6673-XJ	5	150	100	1
DT6674-XJ	5.5	85	50	1
DT6675-XJ	6	100	60	1
DT6676-XJ	6	150	100	1
DT6677-XJ	6	200	150	1
DT6678-XJ	6.5	100	60	1
DT6679-XJ	6.5	150	100	1
DT6680-XJ	7	100	60	1
DT6681-XJ	7	150	100	1
DT6682-XJ	8	120	80	1
DT6683-XJ	8	200	150	1
DT6684-XJ	9	120	80	1
DT6685-XJ	10	120	80	1
DT6686-XJ	10	200	150	1
DT6687-XJ	12	150	100	1
DT6688-XJ	12	200	150	1
DT6689-XJ	13	150	100	1
DT6690-XJ	14	150	100	1
DT6691-XJ	14	200	150	1
DT6692-XJ	16	150	100	1
DT6693-XJ	16	200	150	1



DT6956



DT7928B

## SETS

Article number	Description
DT6956-QZ	5-pcs. set in plastic cassette - Ø 4, 5, 6, 8, 10 mm
DT7928B-QZ	19-pcs. set in the mini safe with EXTREME stone drill Ø 4, 5, 5.5, 6, 7, 8 mm / Bits 25 mm: 4x Ph2, 4x Pz2 / 50 mm: Ph2, Pz2, SL5.5 /magnetic holder, magnetic holder with guide sleeve, in blister packaging.