

Air Cylinder: Standard Double Acting, Double Rod **C75W Series** ø32, ø40

RoHS

How to Order

Double acting, Double rod **C D 75WE 32 - 100 C J L V - B - M9BW**

Built-in magnet

Nil	None
D	Built-in magnet

Bore size

32	32 mm
40	40 mm

Cylinder stroke [mm]
Refer to the next page for standard strokes.

Cushion

Nil	Rubber bumper (Standard)
C	Air cushion

Rod boot

Nil	Without rod boot
J	Nylon tarpaulin (One end)
K	Heat resistant tarpaulin (One end)
JJ	Nylon tarpaulin (Both ends)
KK	Heat resistant tarpaulin (Both ends)

Mounting bracket*1

Nil	None
L	Single foot
M	Double foot
G	Flange
U	Trunnion
N	Clevis

Applicable mounting bracket

Action	Mounting bracket				
	L	M	G	U	N
Rubber bumper	●	●	●	●	●
Air cushion	●	●	●	●	●

Auto switch

Nil	Without auto switch
-----	---------------------

* For applicable auto switches, refer to the table below.
* Auto switches are shipped together with the product.

Auto switch mounting type*1

A	Rail mounting
B	Band mounting

*1 The symbol is "Nil" for no magnet.

Number of auto switches

Nil	2
S	1
n	n

Made to order
For details, refer to page 65.

Accessory*1

Nil	None
V	Rod end

*1 Refer to Mounting Brackets/Accessories on page 66 for details of accessories.
* Accessory is shipped together with the product.

Applicable Auto Switches/Refer to the Web Catalog or Best Pneumatics No. 2-1 for further information on auto switches.

Type	Special function	Electrical entry	Indicator light	Wiring (Output)	Load voltage		Auto switch model				Lead wire length [m]					Pre-wired connector	Applicable load	
Solid state auto switch		Grommet	Yes	3-wire (NPN)	5 V, 12 V	—	M9NV	M9N	F7NV	F79	●	●	●	○	—	○	IC circuit	Relay, PLC
		3-wire (PNP)		M9PV			M9P	F7PV	F7P	●	●	●	○	—	○			
	Connector	2-wire		12 V	M9BV		M9B	F7BV	J79	●	●	●	○	—	○	—		
		—			H7C		J79C	—	●	—	●	●	●	—	—			
	Diagnostic indication (2-color indicator)	Grommet		3-wire (NPN)	5 V, 12 V		M9NWV	M9NW	F7NWV	F79W	●	●	●	○	—	○	IC circuit	
				3-wire (PNP)			M9PWV	M9PW	—	F7PW	●	●	●	○	—	○		
	Water resistant (2-color indicator)	Grommet		2-wire	12 V		M9BWV	M9BW	F7BWV	J79W	●	●	●	○	—	○	—	
				3-wire (NPN)			M9NAV*1	M9NA*1	—	—	○	○	●	○	—	○		
	With diagnostic output (2-color indicator)	Grommet		3-wire (PNP)	5 V, 12 V		M9PAV*1	M9PA*1	—	—	○	○	●	○	—	○	IC circuit	
				2-wire			M9BAV*1	M9BA*1	F7BAV*1	F7BA*1	○	○	●	○	—	○		
		Connector	4-wire (NPN)	5 V, 12 V	—	H7NF	—	F79F	●	—	●	○	—	○	IC circuit			
Reed auto switch		Grommet	Yes	3-wire (NPN equivalent)	—	5 V	—	A96V	A96	—	A76H	●	—	●	—	—	IC circuit	Relay, PLC
								—	200 V	—	—	A72	A72H	●	—	●	—	
		Connector	No	2-wire	24 V	12 V	100 V	A93V*2	A93	A73*2	A73H*2	●	●	●	●	—	—	
							100 V or less	A90V	A90	A80	A80H	●	—	●	—	—	—	
		Diagnostic indication (2-color indicator)	Grommet	Yes	24 V or less	—	—	C73C	A73C	—	—	●	—	●	●	●	—	
	—					—	C80C	A80C	—	—	●	—	●	●	●	—	—	
			Connector	—	—	—	—	A79W	—	—	—	●	—	●	—	—	—	

*1 Water resistant type auto switches can be mounted on the above models, but SMC cannot guarantee water resistance.

Please contact SMC regarding water resistant types with the above model numbers.

*2 1 m lead wire is only applicable to the D-A93.

* Lead wire length symbols: 0.5 m..... Nil (Example) M9NW 5 m..... Z (Example) M9NWZ
1 m..... M (Example) M9NWM None..... N (Example) H7CN
3 m..... L (Example) M9NWL

* Since there are other applicable auto switches than listed above, refer to page 111 for details.

* Solid state auto switches marked with "○" are produced upon receipt of order.

* D-A9□/M9□/A7□/A80□/F7□/J7□ auto switches are shipped together, but not assembled. (For band mounting, only the auto switch mounting brackets are assembled before shipment.)