

Series SY3000/5000

Manifold Parts No.

No.	Description	Part no.		Note
		SS5Y3-10/11/12	SS5Y5-(M)10/11/12	
①	Manifold block assembly	Refer to page 137.		Includes ② (1 pc.), ②③, ②④, and ②⑥.
②	SUP/EXH end block assembly	Refer to page 137.		
③	SUP/EXH block assembly	Refer to page 137.		
④	Terminal block box housing assembly	VVQC1000-T0-1		
⑤	Clamp bracket assembly for terminal block box Clamp bracket assembly for EX126 SI unit	SY30M-15-4A		Supplied individually.
⑥	Lead wire connector block assembly	SY30M-14-4A-1-1		34 cores, 0.6 m lead wire
		SY30M-14-4A-1-2		34 cores, 1.5 m lead wire
		SY30M-14-4A-1-3		34 cores, 3 m lead wire
		SY30M-14-4A-2-1		17 cores, 0.6 m lead wire
		SY30M-14-4A-2-2		17 cores, 1.5 m lead wire
		SY30M-14-4A-2-3		17 cores, 3 m lead wire
		SY30M-14-4A-3-1		9 cores, 0.6 m lead wire
		SY30M-14-4A-3-2		9 cores, 1.5 m lead wire
⑦	Circular connector block assembly	SY30M-14-5A		26 pins
⑧	Valve plate	EX600-ZMV2		With mounting screws (2 pcs. of M4 x 6 and 2 pcs. of M3 x 8)
⑨	EX600 SI unit	EX600-SDN1A		DeviceNet™ PNP (Negative common)
		EX600-SDN2A		DeviceNet™ NPN (Positive common)
		EX600-SMJ1		CC-Link PNP (Negative common)
		EX600-SMJ2		CC-Link NPN (Positive common)
		EX600-SPR1A		PROFIBUS DP PNP (Negative common)
		EX600-SPR2A		PROFIBUS DP NPN (Positive common)
		EX600-SEN1		EtherNet/IP™ PNP (Negative common)
		EX600-SEN2		EtherNet/IP™ NPN (Positive common)
		EX600-SEC1		EtherCAT PNP (Negative common)
		EX600-SEC2		EtherCAT NPN (Positive common)
⑩	EX600 digital input unit	EX600-DXNB		NPN input, M12 connector, 5 pins (4 pcs.), 8 inputs
		EX600-DXPB		PNP input, M12 connector, 5 pins (4 pcs.), 8 inputs
		EX600-DXNC		NPN input, M8 connector, 3 pins (8 pcs.), 8 inputs
		EX600-DXNC1		NPN input, M8 connector, 3 pins (8 pcs.), 8 inputs, with open circuit detection
		EX600-DXPC		PNP input, M8 connector, 3 pins (8 pcs.), 8 inputs
		EX600-DXPC1		PNP input, M8 connector, 3 pins (8 pcs.), 8 inputs, with open circuit detection
		EX600-DXND		NPN input, M12 connector, 5 pins (8 pcs.), 16 inputs
		EX600-DXPD		PNP input, M12 connector, 5 pins (8 pcs.), 16 inputs
		EX600-DXNE		NPN input, D-sub connector, 25 pins, 16 inputs
		EX600-DXPE		PNP input, D-sub connector, 25 pins, 16 inputs
		EX600-DXNF		NPN input, Spring type terminal block, 32 pins, 16 inputs
		EX600-DXPF		PNP input, Spring type terminal block, 32 pins, 16 inputs
	EX600 digital output unit	EX600-DYNB		NPN output, M12 connector, 5 pins (4 pcs.), 8 outputs
		EX600-DYPB		PNP output, M12 connector, 5 pins (4 pcs.), 8 outputs
		EX600-DYNE		NPN output, D-sub connector, 25 pins, 16 outputs
		EX600-DYPE		PNP output, D-sub connector, 25 pins, 16 outputs
		EX600-DYNF		NPN output, Spring type terminal block, 32 pins, 16 outputs
		EX600-DYPF		PNP input/output, Spring type terminal block, 32 pins, 16 outputs
	EX600 digital input/output unit	EX600-DMNE		NPN input/output, D-sub connector, 25 pins, 8 inputs/outputs
		EX600-DMPE		PNP input/output, D-sub connector, 25 pins, 8 inputs/outputs
		EX600-DMNF		NPN input/output, Spring type terminal block, 32 pins, 8 inputs/outputs
		EX600-DMPF		PNP input/output, Spring type terminal block, 32 pins, 8 inputs/outputs
	EX600 analog input unit	EX600-AXA		M12 connector, 5 pins (2 pcs.), 2-channel input
	EX600 analog output unit	EX600-AYA		M12 connector, 5 pins (2 pcs.), 2-channel output
	EX600 analog input/output unit	EX600-AMB		M12 connector, 5 pins (4 pcs.), 2-channel input/output
⑪	EX600 end plate	EX600-ED2		M12 connector, 5 pins, Max. supplied current 2 A
		EX600-ED2-3		M12 connector, 5 pins, Max. supplied current 2 A, with DIN rail mounting bracket
		EX600-ED3		7/8 inch connector, 5 pins, Max. supplied current 8 A
		EX600-ED3-3		7/8 inch connector, 5 pins, Max. supplied current 8 A, with DIN rail mounting bracket
⑫	Clamp bracket for EX600	EX600-ZMA2		With mounting screws (1 pc. of M4 x 20 and 2 pcs. of M4 x 14)
⑬	EX500 SI unit	EX500-Q001		DeviceNet™, PROFIBUS DP, CC-Link, EtherNet/IP™ (Positive common)
		EX500-Q101		DeviceNet™, PROFIBUS DP, CC-Link, EtherNet/IP™ (Negative common)
⑭	EX250 SI unit	EX250-SDN1		DeviceNet™ (Negative common)
		EX250-SPR1		PROFIBUS DP (Negative common)
		EX250-SMJ2		CC-Link (Positive common)
		EX250-SAS3		AS-Interface, 8 in/8 out, 31 slave modes, 2 isolated common type (Negative common)
		EX250-SAS5		AS-Interface, 4 in/4 out, 31 slave modes, 2 isolated common type (Negative common)
		EX250-SAS7		AS-Interface, 8 in/8 out, 31 slave modes, 1 common type (Negative common)
		EX250-SAS9		AS-Interface, 4 in/4 out, 31 slave modes, 1 common type (Negative common)
		EX250-SCA1A		CANopen (Negative common)
⑮	EX250 input block	EX250-SEN1		EtherNet/IP™ (Negative common)
		EX250-IE1		M12, 2 inputs
		EX250-IE2		M12, 4 inputs
		EX250-IE3		M8, 4 inputs
⑯	EX250 end plate assembly	EX250-EA1		With mounting screws (2 pcs. of M3 x 10)
⑰	Clamp bracket assembly for EX250	SY30M-15-3A		Supplied individually.