




Technical data

4T-LM503349

Single row tapered roller bearings

Mounted cone, sheet metal cage

Visual(s)



Product definition

d	46 mm
B	18 mm
d1	61 mm
e	0.4
Y2	1.49
Y0	0.82
Brand	NTN

Product performance

Dynamic load, C	51 kN
Rating life coefficient, A2	1.4
Static load, C0	71 kN
Fatigue limit load, Cu	8.7 kN
Nlim (oil)	6,300 Tr/min
Nlim (grease)	4,700 Tr/min
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.45 Hz
Characteristic rolling element frequency, BSF	9.11 Hz
Characteristic outer ring frequency, BPF0	11.19 Hz
Characteristic inner ring frequency, BPFI	13.81 Hz

Abutment dimensions

ra max

3.94 mm

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

$F_a / F_r \leq e$		$F_a / F_r > e$	
X	Y	X	Y
1	0	0.4	Y2

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X_0	Y_0
0.5	Y0

If $P_0 < F_r$, then use $P_0 = F_r$

The values for e, Y2 and Y0 are shown in the above table