


GE-M-ED

Male Connector

24° Flareless / Metric with EOlastic Seal



DIN 3852-1, form E

TUBE FITTING PART #	END SIZE		d7 (mm)	i (mm)	l1 (mm)	L1 (mm)	S1 (mm)	S2 (mm)	STANDARD Pressure Rating (bar)				
	1	2							EO		EO-2		
	(mm)	Metric							CF	71	MS	CF	71
GE06LMED	6	M10 x 1	14	8	8.5	23	14	14	315	315		315	
GE08LMED	8	M12 x 1.5	17	12	10.0	25	17	17	315			315	
GE10LMED	10	M14 x 1.5	19	12	11.0	26	19	19	315			315	
GE12LMED	12	M16 x 1.5	22	12	12.5	27	22	22	315	315		315	
GE12LM18X1.5ED	12	M18 x 1.5	24	12	12.5	27	24	22	315			315	
GE12LM22X1.5ED	12	M22 x 1.5	27	14	14.0	29	27	22	315			315	
GE15LMED	15	M18 x 1.5	24	12	13.5	29	24	27	315			315	
GE15LM22X1.5ED	15	M22 x 1.5	27	14	15.0	30	27	27	315			315	
GE18LMED	18	M22 x 1.5	27	14	14.5	31	27	32	315			315	
GE22LMED	22	M26 x 1.5	32	16	16.5	33	32	36	160			160	
GE28LMED	28	M33 x 2	40	18	17.5	34	41	41	160			160	
GE35LMED	35	M42 x 2	50	20	17.5	39	50	50	160	160			
GE42LMED	42	M48 x 2	55	22	19.0	42	55	60	160			160	
GE06SMED	6	M12 x 1.5	17	12	13.0	28	17	17	630			630	
GE08SMED	8	M14 x 1.5	19	12	15.0	30	19	19	630	630		630	
GE10SMED	10	M16 x 1.5	22	12	15.0	31	22	22	630			630	
GE12SMED	12	M18 x 1.5	24	12	17.0	33	24	24	630			630	
GE14SMED	14	M20 x 1.5	26	14	19.0	37	27	27	630			630	
GE16SMED	16	M22 x 1.5	27	14	18.5	37	27	30	400			400	
GE20SMED	20	M27 x 2	32	16	20.5	42	32	36	400	400		400	
GE25SMED	25	M33 x 2	40	18	23.0	47	41	46	400			400	
GE30SMED	30	M42 x 2	50	20	23.5	50	50	50	400				
GE38SMED	38	M48 x 2	55	22	26.0	57	55	60	315			315	

For EO-2 part number, insert "Z" between size and pressure series.

Example: GE06ZLMEDCF

Dimensions and pressures for reference only, subject to change.