




Technical data

NJ2204ET2XC3

Single row cylindrical roller bearings

Single row cylindrical roller bearing, single direction for axial loads, separable, polyamide cage.

Visual(s)



Product definition

d	20 mm
D	47 mm
B	18 mm
E	41.5 mm
F	26.5 mm
d1	29.5 mm
rs min	1 mm
r1s min	0.6 mm
Radial clearance class	C3
Mass (without HJ ring)	0.14 kg
Brand	NTN

Product performance

Dynamic load, C	30.5 kN
Static load, C0	28.3 kN
Fatigue limit load, Cu	3.45 kN
Nlim (oil)	16,000 Tr/min
Nlim (grease)	14,000 Tr/min
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.39 Hz
Characteristic rolling element frequency, BSF	4.31 Hz
Characteristic outer ring frequency, BPF0	4.29 Hz
Characteristic inner ring frequency, BPFI	6.71 Hz

Abutment dimensions

da min	25 mm
da max	26 mm
dc min	32 mm
Da max	42 mm
ra max	1 mm

Calculation factors

Equivalent dynamic radial load

$$P = Fr$$

Equivalent static radial load

$$Po = Fr$$