



The Timken Company

4500 Mt Pleasant St. NW


N. Canton, OH 44720

Phone: (234) 262-3000

E-Mail: CustomerCAD@timken.com • **Web site:** www.timken.com

Part Number 26126, Tapered Roller Bearings - Single Cones - Imperial

This is the most basic and most widely used type of tapered roller bearing. It consists of two main separable parts: the cone (inner ring) assembly and the cup (outer ring). It is typically mounted in opposing pairs on a shaft.



[Specifications](#) | [Dimensions](#) | [Abutment and Fillet Dimensions](#) | [Basic Load Ratings](#) | [Factors](#)

Specifications

Series	26000
Cone Part Number	26126
Design Units	Imperial
Cage Type	Stamped Steel
C1 - Dynamic Radial Rating (Two-Row, 1 million revolutions)¹	23000 lbf 102000 N
C90(2) - Dynamic Radial Rating (Two-Row, 90 million revolutions)²	5960 lbf 26500 N



Dimensions

d - Cone Bore	1.26 in 32.004 mm
----------------------	----------------------

B - Cone Width	0.7450 in 18.923 mm
-----------------------	------------------------

Abutment and Fillet Dimensions

R - Cone Backface "To Clear" Radius³	0.060 in 1.5 mm
--	--------------------

da - Cone Frontface Backing Diameter	1.48 in 37.5 mm
---	--------------------

db - Cone Backface Backing Diameter	1.56 in 39.5 mm
--	--------------------

Ab - Cage-Cone Frontface Clearance	0.09 in 2.3 mm
---	-------------------

Aa - Cage-Cone Backface Clearance	0 in 0 mm
--	--------------

a - Effective Center Location⁴	-0.16 in -4.1 mm
--	---------------------

Basic Load Ratings

C90 - Dynamic Radial Rating (90 million revolutions)⁵	3420 lbf 15200 N
---	---------------------

C1 - Dynamic Radial Rating (1 million revolutions)⁶	13200 lbf 58800 N
---	----------------------

C0 - Static Radial Rating	13500 lbf 60100 N
----------------------------------	----------------------

C_{a90} - Dynamic Thrust Rating (90 million revolutions)⁷	2110 lbf 9390 N
---	--------------------

Factors

K - Factor⁸	1.62
G1 - Heat Generation Factor (Roller-Raceway)	16.1
G2 - Heat Generation Factor (Rib-Roller End)	10.1
Cg - Geometry Factor⁹	0.063

¹ Based on 1×10^6 revolutions L_{10} life, for the ISO life calculation method.

² Based on 90×10^6 revolutions L_{10} life, for The Timken Company life calculation method. C_{90} and C_{a90} are radial and thrust values for a single-row, $C_{90(2)}$ is the two-row radial value.

³ These maximum fillet radii will be cleared by the bearing corners.

⁴ Negative value indicates effective center inside cone backface.


⁵ Based on 90×10^6 revolutions L_{10} life, for The Timken Company life calculation method. C_{90} and C_{a90} are radial and thrust values.

⁶ Based on 1×10^6 revolutions L_{10} life, for the ISO life calculation method.

⁷ Based on 90×10^6 revolutions L_{10} life, for The Timken Company life calculation method. C_{90} and C_{a90} are radial and thrust values for a single-row, $C_{90(2)}$ is the two-row radial value.

⁸ These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.

⁹ Geometry constant for Lubrication Life Adjustment Factor a_3 .



IMPERIAL UNITS

Number of Rollers Per Row15	TIMKEN® THE TIMKEN COMPANY NORTH CANTON, OHIO USA	26126 Tapered Roller Bearings - Single Cones - Imperial K Factor Dynamic Radial Rating - C90 Dynamic Thrust Rating - Ca90 Dynamic Radial Rating - C1 1.62 3420 2110 13200 lbf lbf lbf lbf
--	---	--