




Technical datasheet

NU322ET2C3

Single row cylindrical roller bearings

Single row cylindrical roller bearing, floating, separable, polyamide cage

Visual(s)



Product definition

d	110 mm
D	240 mm
B	50 mm
E	211 mm
F	143 mm
rs min	3 mm
r1s min	3 mm
Radial clearance class	C3
Mass (without HJ ring)	10.65 kg
Brand	NTN

Product performance

Dynamic load, C	450 kN
Static load, C0	525 kN
Fatigue limit load, Cu	54.1 kN
Nlim (oil)	3,100 rpm
Nlim (grease)	2,700 rpm
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.4 Hz
Characteristic rolling element frequency, BSF	5.01 Hz
Characteristic outer ring frequency, BPF0	5.66 Hz
Characteristic inner ring frequency, BPF1	8.34 Hz

Abutment dimensions

da min	123 mm
da max	140 mm
db min	145 mm
Da max	227 mm
ra max	2.5 mm
r1a max	2.5 mm

Calculation factors

Equivalent dynamic radial load

$$P = F_r$$

Equivalent static radial load

$$P_0 = F_r$$