


The Timken Company 4500 Mt Pleasant St. NW

N. Canton, OH 44720 **Phone:** (234) 262-3000

E-Mail: <u>CustomerCAD@timken.com</u> • Web site: <u>www.timken.com</u>

Part Number UCFC204, UCFC 200 Piloted Round Flanged Housed Units - Set Screw Locking






<u>Specifications</u> | <u>Dimensions</u> | <u>Basic Load Ratings</u>


Specifications -				
	Bearing Number	UC204		
	Shaft Size d	20 mm		
	Weight	1.5 lb 0.70 Kg		
	UPC Code	087796076013		
	Locking Style	Set Screw Locking		
	Housing Construction	Round Flange		
	Housing Construction	Round Flange		

Dir	nensions		-
	Total Height L	100.00 mm 3.937 in	
	Pilot Outside Diameter H3	62 mm	

Bolt Circle Diameter J	78.00 mm 3.071 in
Bolt Hole Spacing J1	55.10 mm 2.169 in
Bolt Hole Size N	12 mm 0.472 in
Flange Width A1	20.50 mm 0.807 in
Center of Bearing from Housing End A2	10.00 mm 0.394 in
Pilot Width A3	5.00 mm
Inner Ring Width B	31.00 mm 1.220 in
Center of Bearing from Bearing End S	12.7 mm 0.500 in
Dimension A ₄	28.30 mm 1.125 in

Bas	ic Load Ratings		-
	Static Load Rating	1495 lbf 6650 N	
	Dynamic Load Rating	2878 lbf 12800 N	





Bearing Number	UC204			
Load Ratings - C _r	2878	lbf	12800	N
Load Ratings - C _{0r}	1495	lbf	6650	N
Weight	1.5	lb	0.7	kg
Bolt Size	M10			

THE TIMKEN COMPANY NORTH CANTON, OHIO USA

UCFC204

UCFC 200 Piloted Round Flanged Housed
Units - Set Screw Locking

Every reasonable effort has been made to ensure the accuracy of the information contained in this writing, but no liability is accepted for errors, omissions or for any other reason.

FOR DISCUSSION ONLY