

SAFETY SHOES DURANGO S1P SRC

Reference 867127 to 867139

Standard : EN ISO 20345 : 2011 S1P SRC A

Size : from 36 to 48

Composition :

UPPER : Soft suede leather with textile inserts

LINING : WingTex air tunnel textile lining material

SAFETY TOE CAP : AirToe Composite perforated safety toe cap with breathable membrane

PIERCE-RESISTANCE : The exclusive pierce-resistant « no metal » midsole, in comparison to the classical steel midsole is lighter, more flexible and safe since it can be directly stitched to the upper, therefore protecting the entire sole area. Offer pierce resistance of the sole 1100 N, in accordance to recent legislation.

FOOTBED : Action Dry anatomic, breathable footbed, in EVA support with textile material

SOLE : Soft P.U. comfort inner layer

OUTER SOLE : Antislip, antistatic and hard wearing P.U.

LAST : Natural Confort 11 Mondopoint

Weight : 560 g (one foot weight size 42)



SLIP RESISTANCE SRC :

Test floor Ceramics lubricant water+detergent **SRA**

0.41 Flat

0.34 Heel contact angle 7°

Test floor Steel Lubricant Glycerin **SRB**

0.22 Flat

0.17 Heel contact angle 7°

SLIP RESISTANCE REQUIREMENTS ACCORDING TO THE EN ISO 20345:2011 METHOD REQUESTED BY EN 13287:2012