

# Reciprocating Saw LXT®

## DJR186RTE

18V • 0 – 2 800 min<sup>-1</sup> • 32 mm

### Efficient basic reciprocating saw

An efficient reciprocating saw for spark-free cutting of metal and demolition work. Stroke length of 32 mm and stroke rate of 0 – 2 800 min<sup>-1</sup> with continuous control from the switch. Quick-release blade attachment. Two 5.0 Ah batteries and a fast charger in a case.



### Technical specifications

Voltage LXT	✓
Nominal Battery Voltage	18 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Strokes per Minute (SPM)	0 - 2800 min <sup>-1</sup>
Length of Stroke	32 mm
Max. Cutting Capacity in Wood (90°)	255 mm
Max. Cutting Capacity in Steel Pipe	130 mm
Sound Power Level (L <sub>WA</sub> )	95 dB(A)
Sound Pressure Level (L <sub>pA</sub> )	84 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level, Cutting Boards	13,0 m/s <sup>2</sup>
Vibration Uncertainty (K Factor), Cutting Boards	1,5 m/s <sup>2</sup>
Vibration Level, Cutting Wooden Beam	12,5 m/s <sup>2</sup>
Vibration Uncertainty (K Factor), Cutting Wooden Beam	1,5 m/s <sup>2</sup>

**EAN 0088381806725**

Link to product - [www.makita.com](http://www.makita.com)

### User benefits

- Compact and lightweight for reduced operator fatigue
- Slim design with rubberised grip for comfort
- Tool-less blade change and shoe adjustment
- eXtreme Protection Technology (XPT) is engineered for improved dust and water resistance for operation in harsh conditions
- Battery protection system automatically shuts off power when the battery level is low



# Related products

Standard AC

821620-5

Plastic Carrying Case



Standard MA

BL1850B (2x)

Battery LXT® 5,0 Ah



DC18RC

Battery Charger LXT®



Optional AC

821620-5

Plastic Carrying Case



B-05169

Reciprosaw Blade 152 x 0,9 mm



Other

User manual

Parts drawing