

How to Order

● How to order solenoid valves For plug-in (Common for both with and without power supply terminals)

SZ3 1 60 5 LOZ C6

Type of actuation ●

1	2 position single solenoid
2	2 position double solenoid
3	3 position closed center
4	3 position exhaust center
5	3 position pressure center
A	4 position dual 3 port valve: N.C./N.C.
B	4 position dual 3 port valve: N.O./N.O.
C	4 position dual 3 port valve: N.C./N.O.

● Rated voltage

5	24 VDC
6	12 VDC

- When using on a manifold with power supply terminals, be sure to match with the manifold's voltage specifications.

● Back pressure check valve

Nil	None
K	Built-in

- The built-in back pressure check valve type has an effective area approximately 20% smaller.
- The 3 position closed center and 3 position pressure center are not available with back pressure check valve.

● Pilot type

Nil	Internal pilot
R	External pilot

- The 4 position dual 3 port valve is not available with external pilot specifications.

● Switch specifications

Nil: Without switch

J: With switch

* For switch operation, refer to page 1-3-8.

● Common specifications

Nil	Positive common
N	Negative common

- When using on a manifold with power supply terminals, be sure to match with the manifold's common specifications.

Manual override ●

Nil: Non-locking push type

D: Push-turn locking slotted type

● A, B port size

C4: One-touch fitting for ø4
C6: One-touch fitting for ø6

M5: M5 x 0.5

Elbow fitting assembly (Upward)
L4: ø4 elbow fitting assembly
L6: ø6 elbow fitting assembly

Elbow fitting assembly (Downward)
B4: ø4 elbow fitting assembly
B6: ø6 elbow fitting assembly