



How to Order

VXD2 3 2 A A

Size—Valve type			Body material/Port size/Orifice diameter			
Symbol	Size	Valve type	Symbol	Body material	Port size	Orifice diameter
3	8A 10A 15A	N.C.	A	C37	1/4	10
			B		3/8	
			C		1/2	
			D		1/4	
A		N.O.	E	Stainless steel	3/8	
			F		1/2	
4	10A 15A	N.C.	G	C37	3/8	15
B		N.O.	H	Stainless steel	1/2	
			J		3/8	
			K		1/2	
5	20A	N.C.	L	C37	3/4	20
C		N.O.	M	Stainless steel		
6	25A	N.C.	N	C37	1	25
D		N.O.	P	Stainless steel		
7	32A	N.C.	Q	CAC407	32A Flange	35
E		N.O.				
8	40A	N.C.	R	CAC407	40A Flange	40
F		N.O.				
9	50A	N.C.	S	CAC407	50A Flange	50
G		N.O.				

Common Specifications

Seal material	NBR
Coil insulation type	Class B
Thread type	Rc*

* For body size 32A or more, the ports will be the flange type.

Voltage/Electrical entry

Symbol	Voltage	Electrical entry
A	24 VDC	Grommet
B	100 VAC	Grommet (With surge voltage suppressor)
C	110 VAC	
D	200 VAC	
E	230 VAC	
F	24 VDC	DIN terminal (With surge voltage suppressor)
G	24 VDC	
H	100 VAC	
J	110 VAC	
K	200 VAC	Conduit terminal (With surge voltage suppressor)
L	230 VAC	
M	24 VDC	
N	100 VAC	
P	110 VAC	Conduit (With surge voltage suppressor)
Q	200 VAC	
R	230 VAC	
S	24 VDC	
T	100 VAC	Flat terminal
U	110 VAC	
V	200 VAC	
W	230 VAC	
Y	24 VDC	
Z	Other voltages and electrical option	

For other special options, refer to page 668.

Special voltage	24 VAC
	48 VAC
	220 VAC
	240 VAC
	12 VDC
DIN terminal with light	
Conduit terminal with light	
Without DIN connector	
Applicable to deionized water (Seal material: FKM)	
Seal material: EPDM	
Oil-free	
G thread	
NPT thread	
With bracket	
Special electrical entry direction	