

60°C masking adhesive tape 25 & 50 mm x 50 m

Item #	EAN	Width
886628	3660338400377	25 mm
886629	3660338400384	50 mm



Description

100µm semi-crepe paper tape coated with a rubber based adhesive system, recommended for general purpose indoor masking applications. Interior application only. Clean removal at room temperature. Smooth and controlled unwind. Good peel adhesion. Good shear and holding strength. Good paint flake resistance. No staining. Resistant to mild chemicals, lacquers, solvents and water.

Applications

Light weight bundling. Professional painters and plasterers masking tape for indoor use. Suitable for brush, roller and spray applications. Drying in room temperature condition. Suitable for general purpose indoor bonding, holding, sealing and masking applications (24 hours).

Characteristics

Technical attribute	Nominal value ref. 886628	Nominal value ref. 886629	Test Method
Width	25 mm	50 mm	
Length	50 m	50 m	
Temperature resistance	60°C		
Total thickness	0,1 mm		AFERA 5006
Tensile Strength	35 N/cm		AFERA 5004
Elongation at Break	8%		AFERA 5004
Adhesion to Steel	2,5 N/cm		AFERA 5001

Instructions & storage

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants. Masking tapes are not suitable for outdoor exposure and should not be submitted to prolonged periods of sunlight, as tapes may become difficult to remove. Clean removal may also vary with surface type, lacquers, primers and paints nature and the temperature of the surface at removal. For best results, remove the tape as soon as possible after applying the paints pulling it slowly at a 45° angle with constant speed. The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Storage temperature between +10°C and +30°C. Under these conditions, the storage life of the tape in a temperate climate will be at least one year.

Packaging

- 1 unit