



EP40	G	DIN 5156	Normal		2.5XD	HSS-E		B 3.5-5			
EP41	G	DIN 5156	Normal		2.5XD	HSS-E		B 3.5-5			ST

EP40 EP41

- G(BSP) Machine Tap Spiral Point
- G(BSP) Maschinen-Gewindebohrer, geradegenutet mit Schälanschnitt
- G(BSP) Machinetappen met schilaansnijding
- G(BSP) Tarauds machine Coupe gun
- G(BSP) Machos de máquina Entrada en hélice
- G(BSP) Macho de Máquina Entrada Helicoidal

EP40	▪	1.1	1.2	1.3	1.4	1.5	6.1	6.3	7.1	7.2	7.3	7.4	
	•	1.6	3.1	3.2	3.3	3.4	4.1	4.2	5.1	5.2	6.2	8.1	
EP41	▪	1.1	1.2	1.3	1.4	1.5	2.1	2.2					
	•	1.6	2.3	3.1	3.2	3.3	3.4						



G(BSP)	TPI	d ₁ nom mm	l ₁ mm	l ₂ mm	d ₂ Ø mm	□ a mm	l ₃ mm	z		EP40	EP41
1/8	28	9.728	90	18	7	5.5	8	3	8.8	EP401/8	EP411/8
1/4	19	13.157	100	21	11	9.0	12	3	11.8	EP401/4	EP411/4
3/8	19	16.662	100	21	12	9.0	12	4	15.25	EP403/8	EP413/8
1/2	14	20.955	125	24	16	12.0	15	4	19	EP401/2	EP411/2
5/8	14	22.911	125	24	18	14.5	17	4	21	EP405/8	EP415/8
3/4	14	26.441	140	28	20	16.0	19	4	24.5	EP403/4	EP413/4
7/8	14	30.201	150	28	22	18.0	21	4	28.25	EP407/8	EP417/8
1"	11	33.249	160	30	25	20.0	23	4	30.75	EP401	EP411