

Reciprocating Saw LXT®

DJR186Z

18V • 0 − 2 800 min⁻¹ • 32 mm

Efficient basic reciprocating saw

An efficient reciprocating saw for spark-free cutting of metal and demolition work. Stroke length of 32 mm and stroke rate of 0 – 2 800 min-1 with continuous control from the switch. Quick-release blade attachment. Tool only, battery and charger not included.



<u>LXT</u>

Technical specifications

Voltage LXT

Nominal Battery Voltage

Battery Chemistry (Ni-Cd / Ni-MH / Li-ion ion)

Strokes per Minute (SPM)

Length of Stroke

Max. Cutting Capacity in Wood (90°)

Max. Cutting Capacity in Steel Pipe

Sound Power Level (L_{WA})

√

18 V

Li-ion

0 - 2800 min⁻¹

255 mm

130 mm

95 dB(A)

84 dB(A)

Noise Uncertainty (K Factor)

Vibration Level, Cutting Boards

Vibration Uncertainty (K Factor),
Cutting Boards

Vibration Level, Cutting Wooden Beam

Vibration Uncertainty (K Factor),
Cutting Wooden Beam

12,5 m/s²

Vibration Uncertainty (K Factor),
Cutting Wooden Beam

User benefits

- Compact and lightweight for reduced operator fatigue
- · Slim design with rubberised grip for comfort
- Tool-less blade change and shoe adjustment
- eXtreme Protection Technology (XPT) is engineered for improved dust and water resistance for operation in harsh conditions
- Battery protection system automatically shuts off power when the battery level is low



EAN 0088381806640

Link to product - www.makitauk.com



Sound Pressure Level (L_{DA})

Related products

Optional AC

D_EEEGG	

Reciprosaw Blade 100 x 1,25 mm

B-55588

Reciprosaw Blade 228 x 1,25 mm

B-49834

Reciprosaw Blade 152 x 1.25 mm

B-49856

Reciprosaw Blade 305 x 1.25 mm

B-05169

Reciprosaw Blade 152 x 0,9 mm

B-55588-10

Reciprosaw Blade 228 x 1,25 mm

B-55572

Reciprosaw Blade 152 x 1,25 mm

B-55594

Reciprosaw Blade 305 x 1,25 mm

B-49840

Reciprosaw Blade 228 x 1.25 mm

821620-5

Plastic Carrying Case

B-55572-10

Reciprosaw Blade 152 x 1,25 mm

B-55594-10

Reciprosaw Blade 305 x 1,25 mm



Other

User manual

Parts drawing