

Reelworks - 808 Series

SPRING REWIND HOSE REELS

The 808 series are a high performance spring rewind hose reels constructed in heavy gauge powder coated steel for use in most low/medium and high pressure applications. The 4-position roller guide arm adjusts for wall, overhead or ceiling mounting positions. All reels come supplied with fitted hose.

FEATURES:

- Corrosion resistant powder coating
- Guide arm adjustable handling up to 9 positions
- Multi-position ratchet lock
- Solid 1" steel axle
- Spring fully enclosed and lubricated
- Latching of hose at any length
- All brass swivel assembly



Item	Inlet/Outlet (inch)	Max Pressure (psi/bar)	Hose Capacity		Dimensions (cm)	NW/GW (kgs)
			I.D. (inch)	Length (ft/m)		
Low Pressure Air/Water Reels						
C808-350L	3/8"	300/20	3/8"	50'/15	55H x 22W x 53D	24/26
C808-450L	1/2"	300/20	1/2"	50'/15	55H x 22W x 53D	27/29
C808-466L	1/2"	300/20	1/2"	66'/20	55H x 22W x 53D	27/29
Medium Pressure Air/Water Reels						
C808-350M	3/8"	2250/155	3/8"	50'/15	55H x 22W x 53D	24/26
C808-450M	1/2"	2000/138	1/2"	50'/15	55H x 22W x 53D	26/28
C808-466M	1/2"	2000/138	1/2"	66'/20	55H x 22W x 53D	27/29
High Pressure Grease/Hydraulic Oil Reels						
C808-365H	3/8"	4000/276	3/8"	65'/20	55H x 22W x 53D	31/33



ALL
SUPPLIED WITH
FITTED HOSE

Reelworks
The Reel Experts

Reelworks - 809 Series

SPRING REWIND HOSE REELS

The 809 series are a high performance spring rewind hose reels constructed in heavy gauge powder coated steel for use in most low/medium and high pressure applications. The 4-position roller guide arm adjusts for wall, overhead or ceiling mounting positions. All reels come supplied with fitted hose.

FEATURES:

- Heavy-duty steel construction with corrosion resistant powder coating
- 6 1/2" wide L-shaped base ensures stable support
- Guide arm adjustable for handling up to 9 positions
- Multi-position ratchet lock
- Spring fully enclosed and lubricated
- Wall, ceiling, or floor mounted
- Latching of hose at any length
- All brass swivel assembly

Item	Inlet/Outlet (inch)	Max Pressure (psi/bar)	Hose Capacity		Dimensions (cm)	NW/GW (kgs)
			I.D. (inch)	Length (ft/m)		
Low Pressure Air/Water Reels						
C809-325L	3/8"	300/20	3/8"	25'8	39H x 16W x 29D	13/14.5
Medium Pressure Air/Water Reels						
C809-325M	3/8"	2250/155	3/8"	25'8	39H x 16W x 39D	14.5/16
High Pressure Grease/Hydraulic Oil Reels						
C809-325H	3/8"	4000/276	3/8"	25'8	39H x 16W x 39D	16/17.5



ALL
SUPPLIED WITH
FITTED HOSE



Reelworks
The Reel Experts