


Connecting cable SIM-M8-3WD-5-PU

Part number: 159423

FESTO



 General operating condition

Data sheet

Feature	Value
Conforms to standard	EN 61076-2-104 EN 61984
Electrical connection	3-pin/3-wire Angled socket/open end M8x1/-
Symbol	00991871
Operational voltage range DC	0 V ... 60 V
Operational voltage range AC	0 V ... 60 V
Current rating at 40° C	4 A
Immunity to surge	1.5 kV
Cable length	5 m
Cable characteristic	Standard
Test conditions cable	Bending strength: to Festo standard Test conditions on request Energy chain: > 5 million cycles, bending radius 75 mm
Cable diameter	3.8 mm
Cable structure	3 x 0.25 mm ²
Nominal cross section conductor	0.25 mm ²
Colour code wire insulation	Blue Brown Black
Degree of protection	IP65 IP68
Ambient temperature	-25 °C ... 80 °C
Ambient temperature with moving cable	-5 °C ... 80 °C
CE mark (see declaration of conformity)	To EU Low Voltage Directive In accordance with EU RoHS Directive
CE marking (see declaration of conformity)	To UK RoHS instructions To UK regulations for electrical equipment
LABS (PWIS) conformity	VDMA24364-B2-L
Note on materials	RoHS-compliant Free of halogen Free of phosphoric acid ester
Pollution degree	3
Corrosion resistance class CRC	2 - Moderate corrosion stress
Material cable sheath	TPE-U(PU)

Feature	Value
Cable sheath colour	grey
Material housing	TPE-U(PU)
Housing colour	Black
Material union nut	Nickel-plated brass
Material seals	NBR
Material electrical contact	Gold-plated brass
Material insulating sheath	PP