

TECHNICAL DATASHEET

Update : 27/02/2019

METRIC COARSE HSS-PM HARDLUBE COATED SPIRAL FLUTE



Characteristics

Ref.	EAN	Threading diameter mm	Thread mm	Capacity length mm	Total length mm	Din standard	Square drive adapter mm
870236	3660338238819	M2	0,4	8	45	DIN371	2,1
870237	3660338238826	M2,5	0,45	9	50	DIN371	2,1
870238	3660338238833	M3	0,5	18	56	DIN371	2,7
870239	3660338238840	M4	0,7	21	63	DIN371	3,4
870240	3660338238857	M5	0,8	25	70	DIN371	4,9
870241	3660338238864	M6	1	30	80	DIN371	4,9
870242	3660338238871	M8	1,25	35	90	DIN371	6,2
870243	3660338238888	M10	1,5	39	100	DIN371	8
870244	3660338238895	M12	1,75	18	110	DIN376	7
870245	3660338238901	M14	2	20	110	DIN376	9
870246	3660338238918	M16	2	20	110	DIN376	9
870247	3660338238925	M20	2,5	25	140	DIN376	12
870248	3660338238932	M24	3	30	160	DIN376	14,5
870249	3660338238949	M27	3	30	160	DIN376	16
870250	3660338238956	M30	3,5	35	180	DIN376	18