



# Branching module FRM-H-1/8-D-MINI

Part number: 162788

FESTO



 General operating condition

## Data sheet

| Feature                                                | Value                                                    |
|--------------------------------------------------------|----------------------------------------------------------|
| Mounting position                                      | optional                                                 |
| Design                                                 | Branching module                                         |
| Symbol                                                 | 00991511                                                 |
| Operating pressure                                     | 0.15 bar ... 16 bar                                      |
| Standard nominal flow rate in main flow direction 1->2 | 1100 l/min                                               |
| Operating medium                                       | Compressed air to ISO 8573-1:2010 [7:-:-]<br>Inert gases |
| Corrosion resistance class CRC                         | 2 - Moderate corrosion stress                            |
| LABS (PWIS) conformity                                 | VDMA24364-B1/B2-L                                        |
| Storage temperature                                    | -10 °C ... 60 °C                                         |
| Air purity class at output                             | Compressed air to ISO 8573-1:2010 [7:-:-]<br>Inert gases |
| Media temperature                                      | -10 °C ... 60 °C                                         |
| Ambient temperature                                    | -10 °C ... 60 °C                                         |
| Product weight                                         | 325 g                                                    |
| Pneumatic connection, port 1                           | G1/8                                                     |
| Pneumatic connection, port 2                           | G1/8                                                     |
| Pneumatic connection, port 3                           | G1/4                                                     |
| Pneumatic connection, port 4                           | G1/4                                                     |
| Note on materials                                      | RoHS-compliant                                           |
| Material housing                                       | Die-cast aluminium                                       |