

## G-WELD TIG 2 gloves

Reference	EAN	Size
840056	3660338056116	9
840057	3660338056123	10

**Description:** Protective gloves made entirely from lambskin, with thumb insert. The glove is 35cm long, with a 15cm crispin-type cuff. Combining flexibility and dexterity, these gloves are resistant to contact heat up to 100°C for 25 seconds, as well as convective heat, radiant heat and small splashes of molten metal.

**Use instructions/ Applications:** Protective gloves for mechanical risks. Protective gloves against the risks of heat and fire. For use in dry environments. Argon welding and related techniques. Metal handling. Industrial maintenance.

**Usage limits:** Do not protect against electric shocks caused by faulty equipment or live working. Reduced electrical resistance if wet, dirty or soaked in sweat. No standard method for testing UV penetration, but welders' gloves are designed to limit it. Do not use near moving machinery if tear resistance (level  $\geq 1$ ). No known carcinogens or toxic substances. May cause allergic reactions (natural latex may be present in some cuffs). In the event of a reaction, discontinue use and consult a doctor.

### Storage/Cleaning instructions

Store in a cool, dry place, away from frost and light, in their original packaging. No special care is recommended for these types of gloves. Do not wash gloves.

### Standards & Certification



REGULATION (EU) 2016/425



Regulation 2016/425 on personal protective equipment as brought into UK law and amended



### EN388 :2016 +A1 :2018 Protective gloves against mechanical risks (Levels obtained on the palm)



- 2: Resistance to abrasion (from 1 to 4)
- 1: Resistance to cutting (from 1 to 5)
- 2: Resistance to tears (from 1 to 4)
- 2: Resistance to puncture (1 to 4))
- X: Resistance to cutting sharp objects (TDM EN ISO 13997) (from A to F)

### EN407 :2020 Protective gloves and other hand protective equipments against thermal risks (heat and/or fire) X = Unrealized test



- 4: Resistance to flammability (from 1 to 4))
- 1: Resistance to contact heat (from 1 to 4)
- 4: Resistance to convective heat (from 1 to 4)
- X: Resistance to radiant heat (from 1 to 4)
- 4: Resistance to small projections of liquid metal (from 1 to 4)
- X: Resistance to large projections of molten metal (from 1 to 4)

### Packaging

Quantity by polybag: 12 pairs – Quantity by box: 60 pairs